

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Montmorency

(County)

Located In

Corner Code #

1. Public Land Survey

T

R

2. Property Controlling
in Section

S 15

T

29N

R 3E

12

S 15

T

29N

R 3E

16

3. Miscellaneous
Property in Section

S

T

R

S

T

R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on October 15, 2007 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

12- This corner position was not established during the original government survey.

16- Norman C. Caldwell P.S.#12018 set this corner while surveying in the area 1972.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

12- Established the Northwest corner of the Southwest quarter of the Southeast quarter of section 15 as per B.L.M. instructions for the subdivision of a section.

16- Found 1/2" bar W/P.S. cap#12018

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

12- Set 5/8" X 32" iron rod with P.S. cap #33981

Wit: 8" Cherry S20°E 46.20'
7" Cherry S64°E 68.02'
6" Cherry N56°W 27.36'
1 3/4" Pipe N05°W 45.70'

16- Found 1/2" bar W/ P.S. cap#12018

Wit: P. Pole N30°W 48.32'
18" Tamarack N41°E 56.12'
7" Cedar N10°E 46.84'
5" Spruce S45°W 52.42'
Carsonite Post N10°E 33'

Signed by:

Carl T. Kiiskila

Date:

11-29-07

Surveyor's Michigan License No.:

33981

