

JAN 22 2001

Montmorency County Remonumentation

Liber 00012 Page 0420

SECTION

LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MONTMORENCY
 (County)

Located in: BRILEY Corner Code #

STATE OF MICHIGAN
 MONTMORENCY COUNTY
 Recorded & Filed

11-13-2000 13:32:16

TERESA WALKER
 REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey T 30N R 2E C-7
 T R
 T R
 T R
 T R
 2. Property Controlling S T R
 in Section S T R
 3. Miscellaneous S T R
 Property in Sec. S T R

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, FREDERICK J. KING, in a field survey on MARCH 21, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-7 - CORNER COMMON TO SECTIONS 17, 18, 19 & 20

June 1840 - Orig Post set by Lewis Clason, DS - (1)N31°E-41 lks(27.06') 12" Beech (2)S19°W-47 lks(31.02') 12" Beech- Pg.4:
 1941 - 2 1/2" Conc Mon set by Frank Smith, PS#754 (3)EAST-33.0'-4" Conc Mkr (4)WEST-33.0'-4" Conc Mkr
 May 1974 - Act 132 by L.G.Beauregard, PS#18654 (Surveyor for Scott Eng) - Rec L.1, Pgs 538 1/2 & 539 - Fnd 2 1/2" Conc Mon, se
 by F.Smith (1941) (#3)EAST-33.0'-4" Conc Mon (#4)WEST-33.0'-4" Conc Mon - Set DNR Post & Tag Along Side
 July 1978 - LCRC by R.R.Bischer, PS#22428, Rec L.1, Pg 225 - Fnd 2 1/2" Conc Mon by F.Smith (1941) (#5)N54°E-11.40'-10" Mapl.
 (#6)S04°W-20.06'-12" Lynn (#4)WEST-33.0'-Conc Mon (#3)EAST-33.00'-Conc Mon
 July 1978 - Witnesses furnished by D.E.Porter, PS#15410 - Not Recorded - Fnd Conc Mon - Same Witnesses as LCRC Recorded
 L.1, Pg.225

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-7 - CORNER COMMON TO SECTIONS 17,18,19 & 20

Fnd 5" Conc Mon (Rec. as 2 1/2")
 Witnesses Fnd Rec. 3, 4, 5 & 6



THIS CORNER APPROVED BY COUNTY PEER REVIEW ON JULY 18, 2000. AS THE BEST AVAILABLE EVIDENCE OF THE RE-ESTABLISHMENT OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-7 - CORNER COMMON TO SECTIONS 17, 18, 19 & 20

Placed 3 1/4" Aluminum Montmorency County Re-Mon Cap on fnd 5" Conc Mon. * Corner Is In N-S fence & 5.5' S of
 E-W Fence - Set Treated 2"x4" Alongside.
 (Wit#5) - N54°E - 11.23' (R-11.40") - Set S&T - SE side 12" Maple
 (Wit#3) - EAST 32.87' (B-33.0') - 5" Conc Mon.
 (Wit#6) - S10°E - (RS04°E) - 20.50' (R-20.06') - Set S&T - West side 16" Basswood (Rec as Lynn)
 S55°W - 11.86' - Set S&T - NW side 12" Maple
 (Wit#4) - WEST - 32.92' (R-33.0') - 5" Conc Mon * N35°W - 27.24' - Set S&T - SW side 10" Maple

APPROVED BY
 PEER GROUP

Typical Wit Set = 16-D Spk & Plastic ID Tag #25852

Signed by Frederick J. King
 Surveyor's Michigan License No. 25852

Date October 30, 2000

JUL 18 00

L.B.D.