SURVEY.& REMONUMENTATION

JAN 2 2 2001

Montmorency County Remonumentation

Liber 00012 Page 0430

SEC	TĮ	0	N
-----	----	---	---

For corners in

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

MONTMORENCY	Located in: BRILEY	Corner Code #			
(County)	Located III,	Corner Code #	STA MON	ATE OF MICHIGAN	.,
1. Public Land Survey	T_30NR 2E	G-5		NTMORENCY COUNT corded & Filed	r
	TR				
	ŢR		11-	-13-2000 13:34:5	59
2. Property Controlling	TR S TR		TER	RESA WALKER	
in Section	S TR			ISTER OF DEEDS	
Miscellaneous Property in Sec.	S TR S T P				
. ,	·		R	egister of Deeds Sta	amp & File Number
4 Lot No Book	dod Diet				
4. Lot No, Record 5. Private Claims	ued Flat		A	BCDEFG	_н і јк і і
			1 2		
			3		
FREDERICK J. KING	in a field survey on APRI	L 6 2000 do hereby s	tate that under 4	7 8 9	-101112
conformance with regulations and	above were in				
that the corner points mentioned i	in lines 3. 4 and 5 above upon	ment or by a decree of a Court	of Law and /or 6	18 17 16	15 14 13
Board of Land Surveyors or by recovered, found as expressed below	a Decree of a Court of Law	established, re-established,	monumented, 7		
			8 -1	192021	_222324
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.		9	 		
on and odianogia,			10 3	30 29 28	26 25
			11		
			12 -3	32 33	35 36
A. Description of original mon	ument and accessories and	i/or subsequent restoration);		
G-5 - CORNER COMMON TO SECT					
1941 = 25" Conc. Mon. se	9'- X on huge boulder the by Frank Smith, PS# 1.0'-4" Conc Mkr. attery, PE# 3694 -On F Ine Fnc to E (9)4' S c "W-22.75'-Chiseled "X'	54 - Info obtained fr The at Register of De C.L. Rd to W. (10)3	om L.G. Beauregard eds Fnd Conc M W of C.L. Rd to	d, PS#18654 - (5) don (7)EAST-20 S (11)N23°W-89.	"E-28.2"-13" Bass N45°W-50.0"-4" Co 'Fnc Cor Post. 69'-SE Cor Garage
· ·		91- "X" on huge bould pplied in restoring or reest	er (3)S42°Ē-28.2+- ablishing corner:	# "P	3.6
G-5 - CORNER COMMON TO SECT Fnd 5" Conc Mon (Rec				- 1:/	FREDERICK A
Witnesses : Fnd Rec.					PROFESSIONAL CO
					No.
				A SE	25852
				***	OFE SSIONAL TO
THIS CORNER APPROVED BY COUN ORIGINAL CORNER.	ITY PEER REVIEW ON JUL	18, 2000, AS THE BES	T AVAILABLE EVIDEN	NCE OF THE RE-EST	ABLISHMENT OF THE
C. Description of monument for	corner and accessories es	tablished to perpetuate loc	ating the needless state		
G-5 - CORNER COMMON TO SECTI	ONS 9, 10, 15 & 16	tablished to perpetuate loc	aung the position of th	ie corner:	
Corger Is In E edge G N15 E - 38.68' - Fnd (W11 #3) - S45°E (R-S (W11 #6) - S45°E - 15 (W11 #5) - N45°W - 49	m Montmorency County Firav. Dr. to N & In Li Frav. Dr. to N & In Li S&I #25882 — E side An 42°E & S42°40'E & S43° O' (R-50.0') — Fnd Ti .92' (R-50.0') — Fnd 4 .61' — Fnd Spk & Tag #	e of C.L. Rd to W & 1 chor Pole * EAST - E) 28.00' (R-28.2' & pped & Broken 4" Conc " Conc Mon. * N30"W-	6' W of C.L. Rd. 1 33.09' - Fnd 1&C # 28.52') - Fnd Spk Mon (Appears to 80.76' -SE cor of	f18660. & Tag #25882 - N have been hit by f Brick on Hse #10	Farmers Plow)
Typical Witness Set =	16-D Spike and Plasti	c ID Tag #25852			ER GROUP
1//-/	1.1/2			J	UL 18 00
Signed by 7 NOCONCL	4. 95mg		Date October 30.	2000	J. H.B.
Surveyor's Michigan License No.	25852	·			