

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Montmorency  
(County)

Located In  
Hillman  
(Township)

Corner Code #

1. Public Land Survey T 31N R 3E J-7  
T  
2. Property Controlling in Section S  
S  
3. Miscellaneous Property in Section S T R  
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on JANUARY 25, 2006 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

J-7 GLO-1850 Hiram Burnham set quarter section post.

Witnesses: W. Birch 10" N20°E 10 Links  
Hemlock 10" S70°W 37 Links

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

J-7 Re-established the quarter corner common to sections 14 and 23 by single proportionate measurement midway and online between I-7 and K-7. Accepted as careful and faithful re-establishment of the position of the corner by peer group 8-05-05.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-7 Set a 1" x 32" pipe with standard DNR cap.

Witnesses: Maple 8" N37°E 11.85'  
Maple 9" S55°E 13.73'  
Maple 10" S58°W 25.63'  
Maple 10" N29°W 10.14'  
Carsonite Post North 1.0'  
2 Track Road S73°E 272'  
Placed 60 d spikes in trees (typ.)



Signed by:

*Carl T. Kiiskila*

Date:

2-1-06

Surveyor's Michigan License No.:

33981