

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Montmorency

(County)

Located In

Corner Code #

1. Public Land Survey	T	31N	R	3E	F-8
	T		R		
2. Property Controlling in Section	S	22	T	31N	R 3E 12
	S		T		
3. Miscellaneous Property in Section	S		T		R
	S		T		R

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on July 19, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

F-8 This corner position was not established during the original government survey.

12- This corner position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

F-8 Established the center of section 21 at the intersection of the North-South and East-West quarter lines as per B.L.M. instructions for the subdivision of a section.

12- Established the Northwest corner of the Southwest quarter of the Southeast quarter of section 22 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-8 Set 1" x 32" pipe with standard DNR cap

Wit: 5" Oak	S51°E	18.14'
4" Oak	N15°W	13.29'
8" Triple Maple	N81°W	43.40'
3" Oak	N36°W	36.34'
Blue Carsonite Post	North	1'±

12- Set a 5/8" x 32" rerod with P.S. cap #33981

Wit: 8" White Pine	S83°E	25.05'
5" White Pine	S10°E	50.02'
6" White Pine	N45°W	72.02'
4" White Pine	N12°E	27.25'
Blue Carsonite Post	North	1'±

Signed by:

Carl T. Kiiskila

Date:

2/22/06

Surveyor's Michigan License No.:

33981

