

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MONTMORENCY
(County)

Located In:

Corner Code #

1. Public Land Survey

T 32N R 2E
T R
T R
T R

2. Property Controlling
in Section

S28

T R

1 & 2

3. Miscellaneous
Property in Sec.

S

T R

S

T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

CARL KIISKILA

MARCH 26

97

I, , in a field survey on , 19 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

1

2

(NO EVIDENCE OF G.L.D. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.D. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1

2

ESTABLISHED THE NE COR OF THE NW 1/4 OF THE NW 1/4 SEC 28 AS PER STANDARD BLM INSTRUCTIONS. E-W SMOOTH WIRE IS 6' NORTH, N-S SMOOTH WIRE IS 30' EAST.

ESTABLISHED THE NW COR OF THE NE 1/4 OF THE NE 1/4 OF SECTION 28 AS PER STANDARD BLM INSTRUCTIONS. CENTER OF THE E-W TRAIL ROAD IS 3.5' SO. CENTER OF TRAIL TO THE NORTH IS 26' EAST. E-W SMOOTH WIRE IS 3.5' NORTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1

2

SET 5/8 X 32" REROD W/CAP
RED PINE 4" S59°E 23.96'
JACK PINE 8" S29°E 11.03'
JACK PINE 8" S67°W 9.14'
JACK PINE 7" NORTH 6.22'
SET CARSONITE POST 1' NORTH

SET 5/8" X 32" REROD W/PS CAP
RED PINE 5" S08°W 36.08'
JACK PINE 12" S55°W 36.06'
JACK PINE 3" N53°E 45.26'
JACK PINE 4" N59°W 27.59'
SET CARSONITE POST 4' NORTH



Signed by Carl T Kiiskila
Surveyor's Michigan License No. 33981

Date 8-20-97