

NEWAYGO COUNTY

MAR 1 3 2000

1999 Newaygo County Remonumentation Project REGISTER OF DEEDS

LINDA M. BROWN

SECTION

FILING REQUIREMENT of Act 74, Mich. P.A. 1970, 00 FEB 28 PM 1 18

			· · ·	
For corners in  Newaygo (County)	Located in:	Corner Code#	Linds M.	Brown
1. Public Land Survey	T <u>16N</u> R <u>11W</u> T <u>16N</u> R <u>12W</u> T R T R	A-2 V M-2	,	
Property Controlling     in Section     Miscellaneous	STR STR S_TR		<b>VOL. 2</b>	369
Property in Sec.	STR	R	egister of Deeds Stamp & Fi	ile Number
4. Lot No, Reco	rded Plat		ABCDEFGH	IJKLM
5. Private Claims		······································	2 6 + 5 + 4 + 3	$\frac{1}{2}$ $\frac{1}{1}$
I. Norman L. Ochs	in a field survey on October	14 19 99	3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	<del> - - </del> -
I, Norman L. Ochs , in a field survey on October 14 , 19 99, do hereby certify that under requirements of P. A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented,				11 + 12 -
			5	<del>       </del>
			6 - 18 + 17 + 16 + 15 -	† 14 † 13 †
			8 - 19 + 20 + 21 + 22 -	23 24
recovered, found as expressed b	iisned, re-establisned, monumenti elow:	ed, re-monumented,	9 1 20 21 22	
Note: Not more than 4 corners, all in the same town and range, may be			10 - 30 + 29 + 28 + 27 -	26 + 25 -
recorded on this c	ertificate.	will allu lalige, may be	11 + + + + + + + + + + + + + + + + + +	<del> - - - </del> -
West One Quarter Corner, S East One Quarter Corner, Se	ection 6, Barton Township, Ne ection 1, Home Township, New	ewaygo County, Michigan. vaygo County, Michigan.	12 31 + 32 + 33 + 34 -	35 + 36 -
A. DESCRIPTION OF O	RIGINAL MONUMENT ANI	D ACCESSORIES AND/O	R SUBSEQUENT RESTOR	RATION:
G.L.O. John Hodgson 18 8" White Oak S61°W 32 L 18" White Oak N49°W 27 B. DESCRIPTION OF CO	.inks (21.12')#1 Links (17.82')#2 DRNER EVIDENCE FOUNI	O AND/OR METHOD APP	PLIED IN RESTORING OR	
REESTABLISHING COR  No evidence of G.L.O. pos 6 and on line with remnan the recorded witnesses ar	st or witnesses found. Set o	on line with the Southwest nce. The centerline of Tov	t Corner and the Northwest over-line is 324 feet West. Th	Corner of Section ne condition of
C. DESCRIPTION OF MO THE POSITION OF THE	ONUMENT FOR CORNER CORNER:	AND ACCESSORIES ES	TABLISHED TO PERPETU	JATE LOCATING
Set 4" diameter Harrison o corner and is accepted as	cast iron monument 36" lon a careful and faithful reest	g marked "County Survey ablishment of the position	or" as a substantial marker i of the original corner.	for the quarter
16" Cherry (blazed) S43°\ 12" Maple (blazed) West 4	13°E 26.56' Set spike and b N 30.73' Set spike and bras 46.74' Set spike and brass v plazed) N40°E 46.15' Set sp	s washer in North side of washer in North side of tre	tree,	
Signed by	an Locks	Date Octobe	r 22, 1999	
Norman L. Och Surveyor's Michigan License	No. <u>22439</u>	-	ichigan State Board of Land Surveyo	ors, Jan 28, 1971 ed May 14, 1975
Approved by Peer Review Group Norman I Ochs County Repress		·		vised Jan., 1983

