

MAR 11 1999

LIBER 19350 PG 876

JA-599001674

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

\$ 7.00 MISCELLANEOUS RECORDING
\$ 2.00 REMONUMENTATION
3 JAN 99 8:24 A.M. RECEIPT# BA
PAID RECORDED - OAKLAND COUNTY
G. WILLIAM CADDELL
CLERK/REGISTER OF DEEDS

For corners in

Oakland (County)	Located in: Lyon Township	Corner Code #
1. Public Land Survey	T 1N R 7E	A-8
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Compliance with
ACT 345, P.A. 1990
APPROVED ON: 12-16-98 33
OAKLAND COUNTY REMONUMENTATION
PEER GROUP COMMITTEE
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Bruce Antcliff, in a field survey on December 8 19 98,
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required
in the current manual of survey instructions of the United States Department of the interior, Bureau of
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-8 This corner was not originally set by the G.L.O.

N/A N/A O.C. Tax Maps N/A

Found no record information pertaining to this corner.

Records indicate this corner is not common with M-8, T1N, R6E.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-8 Found 1/2" capped iron #30090 in a marsh (no occupation) 118.84' South of M-8, T1N, R6E. The found iron is within 0.10' of the
midpoint between A-7 and A-9 and is 0.14' West of a line between M-8 and M-9, T1N, R7E.

Measure North 2614.7' to A-7

Measure South 2614.9' to A-9

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-8 Removed capped rebar and set a concrete monument with brass cap stamped "Oakland County Remonumentation P.S. #25826" on
the Township line.

PK Nail & Oakland Co. Remonumentation Tag in S Side 8" Pine S 30° E 19.78'

PK Nail & Oakland Co. Remonumentation Tag in S Side 8" Elm S 75° E 27.55'

PK Nail & Oakland Co. Remonumentation Tag in N Side 6" Pine N 90° E 4.35'

PK Nail & Oakland Co. Remonumentation Tag in W Side 6" Pine S 30° W 20.53'

Livingston County Mon. North 118.84'

The selected location is accepted by the Contractor and is generally accepted by professional
surveyors as the best available evidence of the position of the original corner.

Signed by Bruce Antcliff

Date 12-22-98

EARTH TECH

Surveyor's Michigan License No. 25826

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

700 FILE
200

