

LIBR 19351PG013

JA 5 99 001 704

JAN 12 1999

# LAND CORNER RECORDATION CERTIFICATE

## Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

SECTION

Oakland  
(County)Located in: Lyon  
Township

Corner Code #

1. Public Land Survey

T 1N R 7E L-3

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Bruce Antcliff, in a field survey on December 8 19 98, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-3	1816	Holmes	G.L.O.	Set Post
	1966	N/A	MDOT Highway Plans	5/8" Iron Rod
	N/A	N/A	O.C. Tax Maps	N/A

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-3 Found a 5/8" rebar in a marsh 600' ± North of I-96. Checks closely with distance shown on MDOT Highway Plans. Also checks two remaining witnesses from MDOT Highway Plans. The found iron is within 0.6' of the midpoint. No other information on record.

MDOT Highway Plans

3" Sycamore N 42° E 22.13 (m. to C/L 12" = 22.1')

4" Sycamore N 57° E 27.29' (m. to C/L 12" = 27.15')

Measure East 2643.77' to M-3 (G.L.O. = 2651.55')

Measure West 2645.0' to K-3 (G.L.O. = 2651.55') (MDOT (1966) = 2650.0' ±)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-3 Replaced rebar with a 4" x 36" concrete monument with brass cap stamped "Oakland County Remonumentation P.S. #25826."

PK Nail &amp; Oakland Co. Remonumentation Tag in E Side 8" Oak N 10° W 11.84'

PK Nail &amp; Oakland Co. Remonumentation Tag in E Side 12" Sycamore N 45° E 22.00'

PK Nail &amp; Oakland Co. Remonumentation Tag in S Side 30" Oak N 80° E 68.15'

PK Nail &amp; Oakland Co. Remonumentation Tag in N Side 12" Oak S 40° E 57.09'

The selected location is accepted by the Contractor and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

Signed by Bruce Antcliff  
EARTH TECHDate 12-22-98Surveyor's Michigan License No. 25826

\$ 7.00 MISCELLANEOUS RECORDING

\$ 2.00 REMONUMENTATION

3 JAN 99 8:30 A.M.

RECEIPT 8A

PAID

RECORDED - OAKLAND COUNTY

G. WILLIAM CADDELL

CLERK/REGISTER OF DEEDS

Compliance with  
ACT 345, P.A. 1990

APPROVED ON: 12-16-98 SS  
OAKLAND COUNTY REMONUMENTATION  
PEER GROUP COMMITTEE

Register of Deeds Stamp &amp; File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

700 FILE  
200