SURVEY & REMONUMENTATION

Mar 1095040392

MAY - 1 1995

LIBER 15288 PG 478

LAND CORNER RECORDATION CERTIFICATE

For	COMMISSIO	Filing Requirement of Act 74, Mich. P.A. 1970 Commerce Twp.											
—	(County)	Located		Corner Code =##	t	OK -	- T. S	SMI	The same	***************************************			
1.	Public Land Survey	2N 8E E-5 T R T R T R T R T R			APPROV	Compliance with ACT 345, P.A. 1990 APPROVED ON: 12-13-94							
	Property Controlling in Section Miscellaneous Property in Sec.		AKLAND COUNTY REMONUMENTATION PEER GROUP COMMITTEE Register of Deeds Stamp & File Number										
	Lot No , Rec					A B	СВ	E F	G	н і	J	к L	T
	David Pawlaczyk		Decem		94	3 4 7	5	9-	 -1	} 	-2- -11-	+	i -
do l in ti cur Mai abo Cou	hereby certify that under requi ines 1 and 2 above were in c trent manual of survey instruct nagement or by a decree of a C ove were in conformance with to urt of Law; established, re- pressed below:	rements of P.A. 74, onformance with cions of the United ourt of Law and/or the rules of the Mid	Michigan P.A. of regulations and States Departm that the corner p chigan Board of I	1970, the corner point rules therefore as recent of the Interior, Bu points mentioned in lin Land Surveyors or by	ts mentioned quired in the reau of Land nes 3, 4 and 5 a Decree of a d, found as	5 6 13- 7 8 19- 9	29	21-	1 2	5	-14- -23- -26-		13-24-
NO	on this certificate.	ners, all in the s	ame town and	range, may be rec		12 31-	32	33	1-3		_35_	-	- 36-
A.	Description of original mo	onument and acc	cessories and/	or subsequent rest		13	<u></u>				—		
	1815 Post 1992 1/2" Iron in	G.L.O.	A. Holmes	N/A	Notes								
	monument 1992 1/2" Iron in	box Survey	J. Scharl	#19843	L13212 P411								
	monument	box L.C.R.C.	J. Scharl	#19843	L13127 P396								

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A 1/2" iron rod in an existing monument box in asphalt pavement currently occupies this corner. The following witness ties were used to recover and verify this corner's position:

4 ties match L.C.R.C. L13127 P396

Field measurements were made between the following corners:

E-5 to D-5 2643.87 meas. G.L.O. 2641.65 rec. Notes 2665.38 meas. E-5 to E-6 2640.00 G.L.O. Notes rec.

17632

\$ 7.00 MISC RECORDING CHG - IN HOUSE RECEIPT# 1778 10 HAR 95 3:56 P.M. RECORDED - OAKLAND COUNTY PAID SYRWOO, REMON, CHIGERY, THE HOUSER OF STEPS

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I placed a 2" diameter brass cap stamped "Oakland County Remonumentation PS #17632" on the existing 1/2" iron rod in an existing monument box in asphalt pavement.

N.41° W. 56.46' P.K. nail and O.C.R. tag in E. face light pole N.42° E. 51.92 P.K. nail and O.C.R. tag north post boat ramp sign P.K. nail and O.C.R.C tag S.E. face 15" Oak S.36° E. 100.971 S.53° W. P.K. nail and O.C.R.C. tag in S.E. face 6" Oak 88.81'

The selected location is accepted by me and generally accepted by Professional Surveyors as the best available

evidence of the position of the origin nal corner.

Signed by Surveyor's Michigan License No. _

Date 2-16-95

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 20, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983

PAWLACZYK LAND SURVEYOR

NO.

17632