

**COPY**

**For corners in**

Located In: Corner Code #  
West Bloomfield Township

- T2N      R9E      D-1

- 8  
T  
T  
T  
T
- R  
R  
R  
R
- SECRET &  
INFORMATION

- S — T — R —  
 S — T — R —  
 S — T — R —
- [REDACTED] 21 2000

- SECTION <sup>west</sup> bloomfield

\$ 9.00 MISCELLANEOUS RECORDING  
\$ 2.00 REMONUMENTATION  
9 APR 98 1:41 P.M. RECEIPT# 10664  
PAID RECORDED - OAKLAND COUNTY  
LYNN D. ALLEN, CLERK/REGISTER OF DEEDS

APPROVED ON: 3-4-98 JS  
OAKLAND COUNTY REMONUMENTATION  
PEER GROUP COMMITTEE

A. Description of original monument and accessories and/or subsequent restoration:  
1817-GLO Carpenter, D.S.; No post was set  
1.) 1991-Wozniak, PS #15066; LCRC L.11949, Pg.439 – Fnd a Iron Bar  
2.) 1992- Zeimet, PS #9209; LCRC L.12439, Pg.248 – Fnd a Iron Bar, used the same wit as 1991 LCRC

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
1998-Kennedy Surveying, Inc. - Kennedy, PS #17623 - A P.K. Nail was set 2.50 feet West of the existing centerline of Lockhaven Road extending to the North & South, which has a bituminous surface, and 15 feet North of the existing centerline of Hunt Road to the West, which has a gravel surface. Also found a Iron Rod w/2" diameter brass cap stamped Oakland County Remonumentation, PS #31606 in a existing Monument Box 1.00 feet to the East, which is being used and accepte as the South ¼ corner of Section 32, T3N, R9E, Waterford Township (D-13).

Using the existing monumentation as recovered in "HUNTWOOD MEADOWS NO. 1" a plat recorded in Liber 212 of Plats, pages 16 thru 19 of Oakland County Records, and validated by one of the witnesses from the LCRC recorded in Liber 114, page 439 of Oakland County Records.

Field measurements see back side of LCRC

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
D-1 I set a 5/8" x 24" Iron Rod w/2" diameter brass cap stamped Oakland County Remonumentation, PS #17623 in a new Monument Box  
S44°W 55.60' Set PK & Remon Washer SE face Power Pole  
S33°E 114.15' Set PK & Remon Washer SW face 13" Poplar  
N62°W 47.68' SE corner of house #6555  
N61°E 65.84' SW corner of garage #1481  
East 1.00 feet South ¼ corner of Section 32, T3N, R8E, Waterford Township (D-13)

The selected location is accepted by me and is generally accepted by Professional Surveyors the position of the original corner.

Surveyor's Michigan License No.

Date 3-6-98

