

LIBER 18952 PC 314

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oakland
(County)

Located in: Corner Code #
West Bloomfield Township

1. Public Land Survey

T2N R9E E-6
T R
T R
T R
S T R
S T R
S T R
S T R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

4. Lot No. Recorded Plat SECTION
5. Private Claims

\$ 7.00 MISCELLANEOUS RECORDING
\$ 2.00 REMONUMENTATION
16 SEP 98 7:36 A.M. RECEIPT
PAID RECORDED - OAKLAND COUNTY
LYNN D. ALLEN, CLERK/REGISTER OF DEEDS

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 9-16-98 JS
OAKLAND COUNTY REMONUMENTATION
PEER GROUP COMMITTEE

Register of Deeds Stamp & File Num

I, Huston K. Kennedy, in a field survey on June 3, 1998, hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L
1											
2	6		5		4		3		2		1
3											
4	7		8		9		10		11		12
5											
6	18		17		16		15		14		13
7											
8	19		20		21		22		23		24
9											
10	30		29		28		27		26		25
11											
12	31		32		33		34		35		36
13											

- A. Description of original monument and accessories and/or subsequent restoration:
1817-GLO Carpenter, D.S.; Set Post 28" White Oak S75°E 58 Links; 16" White Oak S88 ¾°W 41 1/3 Links
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
1998-Kennedy Surveying, Inc. - Kennedy, PS #17623 - The corner as recovered is in a tree/fence row extending to the No & South and 103 feet ± North of the water's edge of Upper Straits Lake.

HOW THE CORNER WAS RECOVERED

The corner was recovered at the midpoint between E-5 and E-7 and set the corner on the East line of "UPPER STRAITS BEACH" a plat recorded in Liber 55 on pages 51 & 51A of Oakland County Records.

FIELD MEASUREMENTS BETWEEN

E-5 to E-6

GLO = 40 chains or 2640.00 Ft.
No plat or sidwell distances
2665.95 Ft. (GPS-MEA)

E-6 to E-7

GLO = 40 chains or 2640.00 Ft.
No plat or sidwell distances
2665.95 Ft. (GPS-MEA)

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
E-6 I set a 4" diameter Concrete Monument with a ½" Iron w/2" diameter brass cap stamped Oakland Co Remonumentation, PS #17623
N17°W 11.30' Set Mag Nail & Remon Washer SW face 24" Oak South 7.16' found 4" diameter Concrete Monument
N50°E 29.22' Set Mag Nail & Remon Washer NW face 27" Oak
Due South 22.00' Set Mag Nail & Remon Washer East face 19" Oak
Due East 7.65' Set Mag Nail & Remon Washer North face 25" Locust

The selected location is accepted by me and is generally accepted by Professional Surveyors as the position of the original corner.

Signed by: [Signature]
Surveyor's Michigan License No. 17623

Date 7/29/98

