## UBER 18952 PC 316

For corners in		CORNER RECORDATION CER g Requirement of Act 74, Mich. P		98 2
		Outum no Oo do #	\$ 7.00 MISCELLAN	EOUS RECORDING 📜
Oakland (County)	Located In: West Bloomfleid	Corner Code # Township	\$ 2.00 REHUNDIEN	
1. Public Land Survey	T <u>2N</u> R T R	9E 1-8		N. RECEIPT# SAP ROED - CANLAND COUNTY LERK/REGISTER OF DEEDS
Property Controlling in Section     Miscellaneous Property in Sec.	S T R S T R S T R S T R	MEDITION LETTON	1	ince with P.A. 1990
4. Lot No, Re 5. Private Claims	ecorded Plat	SECTION	ACT 345.  APPROVED ON: OAKLAND COUNTY PEER GROU	7 · /6 · 98 JS REMONUMENTATION P COMMITTEE Is Stamp & File Number
requirements of P.A. 74, Mic conformance with regulations United States Department of	higan P.A. of 1970, the corner ; and rules therefore as required the Interior, Bureau of Land Mar led in lines 3, 4 and 5 above we r by a Decree of a Court of	ABY 5 . 1998 o hereby state the points mersioned in the 1 and 2 above in the current manual of survey instructions agement or by a decree of a Court of Law; established, re-established, mon	at under 2 6 5 5 ms of the nw and/or 4 7 8 Michigan	
NOTE: Not more than 2 on this certificat		and range, may be recorded	7 8 19 20 9 10 30 29	21 26 25
1817-GLO Carper Oak N06 % W 16 1.) 1960-Alix, PS witnesses 2.) 1970-Alix, PS 3.) 1979-Mosher 4.) 1987-Stepher	nter, D.S.; Set Post 9" Bi 2/3 Links 3 #8254; Unrecorded Sur ; #8254; Unrecorded Sur , PS #9243; Unrecorded ns, PS #29252; Unrecord	les and/or subsequent restoration: ack Oak S11 ½°E 6 ½ Links; 6 urvey — Object found not stated, a Survey — Object found not stated, a Survey — Object found not stated led Survey — Fnd Concrete Mon	ted, no no witnesses ed nument, no witnesses	13 - 34 - 35 - 36 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
1998-Kennedy Surv "Michigan Conserva fence extending to t Concrete surface, a The tie from I-6 to County Records is a	reying, Inc. — Kennedy, PS a ution Department Public Fisi the South with a tree/fence in and 60 feet West of the exist point the beginning for "Si recorded as 58.75 feet, but		the ground surface, and 0.30 fe chard Lake Road extending to the extending Northeast, which he plat recorded in Liber 92 of plan	e South, which has a as a bituminous surface. ts, on page 22 of Oakle
brass cap stamped	"Michigan Conservation D	over and verify the location of the epertment Public Fishing SHE 63-1	1940)	
Fishing SHE 63-1	und 4" octagon Concrete I 1940) as the best evidence IENTS BETWEEN	Vionument with 4" diameter brass of the original corner position.	cap stamped "Michigan Const	100 11ct
I-6 to I-5 No GLO, corner fa No plat or sidwell	alls in Orchard Lake distances	I-6 to I-7 GLO = 40 chains or 2640.00 F Parcels = 2648.61 Ft. 2646.86 Ft. (GPS-MEA)		2"
I-6 I accept the for Department Pub S24°W 30.20' S6 N71°W 29.35' S6 N16°W 74.90' S6 N02°E 21.30' S6	ound 4° octagon Concret lic Fishing SHE 63-1 19 et Mag Nail & Remon Wa et Mag Nail & Remon Wa et Mag Nail & Remon Wa t Mag Nail & Remon Wa	ssories established to perpetuate k le Monument with 4" diameter b 40) Isher SE face 26" Oak Isher North face 16" Oak Isher SW face 29" Oak Isher East face 19" Oak	Hass cap stamped Michigan	HUSTON KENNEDY PROFESSIONAL SURVEYOR
The selected location the position of the or Signed by:	n is accepted by me and iginal comer.	d is generally accepted by Pro	fessional Surveyors as the large to the	PROFESSIONAL SHOWN IN THE PROFESSIONAL SHOWN
Signed by.	17	673		