

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oakland

(County)

Located in:

Corner Code #

West Bloomfield Township

1. Public Land Survey

T2N R9E I-7

T R

T R

T R

2. Property Controlling in Section

S T R

3. Miscellaneous Property in Sec.

S T R

S T R

SECTION

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Huston K. Kennedy, in a field survey on June 12, 1998 hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1817-GLO Carpenter, D.S.; Set Post 14" Aspen N30 1/2°W 15 1/2 Links; 13" Black Oak S36 1/4°E 47 Links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1998-Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd a cut "x" in the existing centerline of Orchard Lake Road extending to the North &amp; South, which has a concrete surface.

## FIELD MEASUREMENTS BETWEEN

## I-7 to I-8

GLO = 40 chains or 2640.00 Ft.  
"ORCHARD LAKE SQUARE" + Parcels (Sec 15) = 2648.61 Ft.  
2648.86 Ft. (GPS-MEA)

Con't on back side of LCRC

## I-7 to H-7

GLO = 39.80 chains or 2628.80 Ft.  
No plat or sidwell distances  
2651.72 Ft. (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-7 I set a 5/8" x 24" Iron Rod w/2" diameter brass cap stamped Oakland County Remonumentation

Monument Box

Due West 38.28' Set Mag Nail &amp; Remon Washer North face Power Pole

S32°W 156.86' Cut "x" on top nut of Fire Hydrant

S27°E 181.34' Set Mag Nail &amp; Remon Washer NE Face Power Pole

N83°E 44.44' Set Mag Nail &amp; Remon Washer North face Power Pole

The selected location is accepted by me and is generally accepted by Professional Surveyors as the position of the original corner.

Signed by

Date

8-21-98

Surveyor's Michigan License No.

17623

\$ 9.00 MISCELLANEOUS RECORDING

\$ 2.00 REMONUMENTATION

16 SEP 98 7:38 A.M. RECEIPT# 147

PAID RECORDED - OAKLAND COUNTY

LYNN D. ALLEN, CLERK/REGISTER OF DEED

Compliance with  
ACT 345, P.A. 1990

APPROVED ON: 9-16-98 JS  
OAKLAND COUNTY REMONUMENTATION  
PEER GROUP COMMITTEE

Register of Deeds Stamp &amp; File Num

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2												
3												
4												
5												
6												
7												
8												
9												
10												
11												
12												
13												

