

FE2499072816

COPY
Located In
West Block

Oakland

(County)

Located In:

West Bloomfield Township

Corner Code #

1. Public Land Survey

T2N R9E K-12

T R N-14

T R SLOAN

R

T R 12/1/71

T R

2. Property Controlling in Section

3. Miscellaneous
Property in Sec.

4. Lot No. _____, Recorded Plat
5. Private Plat _____

5. Private Claims

SECTION

92.00 MISC RECORDING
92.00 REMONUMENTATION
02/24/1999 09:10:12 A.M. RECEIPT# 3390
PAID RECORDED - OAKLAND COUNTY
G. WILLIAM CADDELL, CLERK/REGISTER OF DEEDS

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 2-17-99 JS
OAKLAND COUNTY REMONUMENTATION
PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

I, Huston K. Kennedy, in a field survey on February 1, 1989 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
1817-GLO Carpenter, D.S.; Set Post 10" Black Walnut N87 ½°E 49 ¾ Links; 12" Poplar S01°E 69 Links
1.) 1962-Oakland County Road Commission Unrecorded Witnesses – Find a stone

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
1999-Kennedy Surveying, Inc. - Kennedy, PS #17623 - The corner as recovered is located 3.30 feet West of the existing centerline of Middle Belt Road extending to the North & South, which has a bituminous surface. A chain link fence extending to the East. The corner was recovered by using the existing monumentation in "FRANKLIN VILLAGE SUBDIVISION NO. 6".

FIELD MEASUREMENTS BETWEEN

FIELD MEASUREMENTS BETWEEN

K-12 & K-11

GLO = 40 chains or 2640.00 Ft.

"FRANKLIN CORNER'S" + Parcels (Sec 36) = 2656.18 Ft.

2655.84 Ft. (GPS-MEA) + Parcels (Sec 35) = 2655.73 Ft.

K-12 to K-13

GLO = 40 chains or 2640.00 Ft.

*FRANKLIN KNOLLS NO. 3" + "FRANKLIN KNOLLS NO. 3" + Parcels (Sec 35) = 2648.09 Ft.

2648.74 Ft. (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner of the building #7020 in a new
K-12 1 set a 5/8" x 24" Iron Rod w/2" diameter brass cap stamped Oakland County Remonumentation, 17623 in a new
Monument Box
N80°E 61.94' Set Mag Nail & Remon Washer North face Power Pole
S23°E 80.77' Set Mag Nail & Remon Washer SW face Power Pole
N32°W 78.89' Set Mag Nail & Remon Washer SW face Power Pole
S33°W 118.20' SE corner of building #7020 (Ameritech)

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by:

Surveyor's Michigan License No.

Date 2-18-99

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYOR'S, JAN. 28, 197
REVISED MAY 14, 197
REVISED JAN., 198
REVISED OCT., 199