URER 19548 PG 784

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Surveyor's Michignan License No.

	Filing Requirement of Act 14, mileting in	\$ 7.00 REMONINENTATION
For corners in		11 FER 99 9:02 A.M. RECEIPT# 3A
Oakland /	Located in: Corner Code #	PAID RECORDED - CAKLAND COPPATY
(County)	West Bloomfield Township	G. WILL IAM CAUDELL
4 Put Sal and Contou	T <u>2N</u> R <u>9E L-11</u>	CLERK/REGISTER OF DEEDS
1. Public Land Survey	TR	
	TR	- T
	S T ORON	Compliance with
2. Property Controlling	ST_RR	ACT 345, P.A. 1990 -==
in Section	S T R 74 0 21 7000	APPROVED ON: 2-3:95 34
3. Miscellaneous	S T R	**************************************
Property in Sec.	and the second s	}
	SECTION	Register of Deeds Stamp & File Numbe
4. Lot No, Recon	ded Plat	ABCDEFGHIJKLM
5. Private Claims		
		2 -6-+-5-+-4-+-3-+-2-+-1
		<u> </u>
Huston K. Kennedy ii	in a field survey on October 27, 1998 do hereby state that und	der 4 7 8 9 10 12 12 12
moultaments of P.A. 74. MICHIGAII	The Utility of the Colorest of the Colorest Colores Of the Colores	the . (
I Initial States Department of the In-	itelior, being of the Michigan	Dan 6 18
that the corner points mentioned in	nterior, Bureau of Land Management or by a decise of a doctor of the Michigan Innes 3, 4 and 5 above were in conformance with the rules of the Michigan Bocree of a Court of Lawr, established, re-established, monument	ted, 7
recovered, found as expressed be	low:	8 19 20 21 22 23 24
•		
NOTE: Not more than 2 con	ners, all in the same town and range, may be recorded	10 30 29 28 27 26 25
on this certificate.		
		11 32 33 36
	nonument and accessories and/or subsequent restoration:	12-31-13/-1-1
2.) 1994-Milletics, P. 3.) 1977-Knapp, PS 4.) 1977-Knapp, PS 5.) 1977-Knapp, PS 6.) B. Description of corner e 1998-Kennedy Surve extending to the Eas	S #29249; LCRC L.15050, Pg.488 – Set a PK Nail S #29249; Survey L.10573, Pg.127 – Object found not stated, #13773 Unrecorded Survey – Object found not stated, widence found and/or method applied in restoring or reestablication, Inc. – Kennedy, PS #17623 – Fnd a PK Nail .50 st & West, which has a bituminous surface. A tree-fence with.	no witnesses no witnesses shing corner: feet North of the existing centerline of Maple Roas row extending to the North, and a old fence line
VAELAARRAN FROM I CE	RC #1 and adjacent plats were used to recover and ver	ify the location of the found PK Nail.
I accepted the found	d PK Nail as the best evidence of the original corner po	rify the location of the found PK Nail.
FIELD MEASURME		' フ "
MCED MEAGORITHM		1 -41 to M-11
L-11 to K-11	0042 64 Et	01 0 40 04 shoins or 2642 64 E1
GLO = 40.04 chains		"KNOLLWOOD HEIGHTS" + "BLOOMFIELD FARM + Parcels (Sec 36) = 2656.85 Ft.
*SOUTH BLOOMFIE	ELD GLENS. + "20014 Proomitiers of the	2656.32 Ft. (GPS-MEA)
. n	·'MAN KAPI	MARTIE OF MICHAEL
Survey recorded in L 2659.30 Ft. (GPS-M	- 2659.50 Ft. Liber 15073, page 127 ≈ 2659.51 Ft.	Marie Commence of the Commence
		ating the position of the conserver HUSTON
L-11 replaced the Remonumentation, S56°E 41.54' Set N N44°W 67.03' Set I N64°E 262.43' Cut	nent for comer and accessories established to perpetuate local found PK Nail with a 5/8" x 24" Iron Rod w/2" diameter per #17623 in a new Monument Box Mag Nail & Remon Washer NE face Power Pole Mag Nail & Remon Washer SE face 12" Locust "x" on top of nut on Fire Hydrant & Mag Nail & Remon Washer NW face 14" Locust	SURVEYOR 17623 17623 17625 176
And the second of the	is accepted by me and is generally accepted by Profe	essional Surveyors as the best available evidence
The selected location the position of the original	is accepted by me and is generally accepted by Piole inal comer.	· · · · · · · · · · · · · · · · · · ·
(/V_	Date	2-4-1999

ø