

# **LAND CORNER RECORDATION CERTIFICATE** **Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

Oakland  
 (County)

Located in:  
 Highland Township

Corner Code #

51133

LIBER 21118 PAGE 129  
 \$7.00 MISC RECORDING  
 \$2.00 REMONUMENTATION  
 02/18/2000 10:03:34 A.M. RECEIPT# 13978  
 PAID RECORDED - OAKLAND COUNTY  
 G. WILLIAM CADDELL, CLERK/REGISTER OF DEEDS

Compliance with  
 ACT 345, P.A. 1990

APPROVED ON: 12-14-99 JKL  
 OAKLAND COUNTY REMONUMENTATION  
 PEER GROUP COMMITTEE

Register of Deeds Stamp &amp; File Number

1. Public Land Survey

T3N R7E M-8

2. Property Controlling  
In Section

S T R SURVEY &amp; RE

3. Miscellaneous  
Property in Sec.

S T R MAR 21 2000

4. Lot No. \_\_\_\_\_ Recorded Plat \_\_\_\_\_ SECTION

5. Private Claims \_\_\_\_\_

I, Huston K. Kennedy, in a field survey on October 15, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

- 1817-GLO Wampler, D.S.; Set Post 12" Maple N14°E 11 Links; 8" Birch S23°E 4 Links;  
 1.) 1998-Kovas, PS #33138; LCRC for (A-8 White Lake Twp.) L.18744, pg.264 - Set a Concrete Monument w/Remon Cap #33138 in a swamp

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 1999-Kennedy Surveying, Inc. - Kennedy, PS #17623 - The corner was recovered on the line between M-9 and A-8 of White Lake Township at the midpoint between M-8 and M-9. The West 1/4 corner of Section 19, T3N, R8E, White Lake Township (A-8) is located 296.92 feet to the South. The corner is 33 feet ± South of a small stream.

## FIELD MEASUREMENTS BETWEEN

### M-8 to A-8

No GLO  
 296.92 Ft. (GPS-MEA)

### M-8 to M-9

GLO = 40 chains or 2640.00 Ft.  
 No recorded distances  
 2659.07 Ft. (GPS-MEA)

### M-8 to M-7

GLO = 40 chains or 2640.00 Ft.  
 No recorded distances  
 2659.07 Ft. (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- M-8 I set a 4" diameter Concrete Monument with a 1/2" Iron Rod 36" long w/2" diameter brass cap stamped Oakland County Remonumentation, PS #17623  
 N21°W 8.48' Set Mag Nail & Remon Washer SE face Yellow Birch  
 S63°E 20.35' Set Mag Nail & Remon Washer SW face 12" Maple  
 N57°E 20.40' Set Mag Nail & Remon Washer SE face 7" Maple  
 N82°W 28.45' Set Mag Nail & Remon Washer NE face 18" Ash  
 North 296.92 feet West 1/4 corner of Section 19, T3N, R8E, White Lake Township (A-8)

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by: \_\_\_\_\_

Date 2-10-2000Surveyor's Michigan License No. 19623