

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Ogemaw

(County)

Located In

Corner Code #

1. Public Land Survey	T		R	
	T		R	
2. Property Controlling in Section	S	21	T	23N R 2E 14
	S			
3. Miscellaneous Property in Section	S		T	R
	S		T	R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on June 22, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

14 - S1/16 Cor. Common to Sec's. 21 & 22, T23N, R2E

Carl R. Johnson P.S.#30083 set this corner by standard by BLM procedure while doing a survey in section 21.

Wit: W. Pine 10" N42°E 23.4'
Oak 8" N23°W 13.0'
J. Pine 12" S16°E 17.5'
W. Pine 5" S22°W 31.7'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

14- Fd. 5/8"x32" rebar with P.S.cap#30083 fitting standard BLM procedure. Corner falls 3' West of N-S C/L 2-track. Found no other evidence to dispute the location for the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

14- 5/8"x32" rebar with P.S.cap#30083

Wit: N33°E 24.03' to set N&T on E side 12" W. Pine
S14°E 41.00' to set N&T on E side 12" Red Maple
S60°W 25.94' to set N&T on SE side 5" Red Oak
N18°W 36.83' to set N&T on NE side 5" W. Pine
East 12.05' to 1/2" x 36" Galv. Pipe set by Land Owner for reference.
Set Blue Carsonite Post with Loc. Tag 10' West



Signed by:

Carl T Kiiskila

Date:

7-9-09

Surveyor's Michigan License No.:

33981