

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

Recd Ogemaw Cnty 081512PM0203

For Corners In:
OGEMAW
(County)

Located In Corner Code #

1. Public Land Survey T R
T R
2. Property Controlling
in Section S 34 T 23N R 3E 16
S T R
3. Miscellaneous
Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on March 8, 2012 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

16 East 1/16 Corner South line Section 34, T23N,R3E

1975 - Certificate of Survey - L.1, p.21 - Norman C. Caldwell,
P.S.#12018 set 1/2" Bar & RLS Cap

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

16 East 1/16 Corner South line Section 34, T23N,R3E

Found 1/2" CIR#12018 per Certificate of Survey,
L.1,pg.21, 6" below grade

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

16 East 1/16 Corner South line Section 34, T23N,R3E
Set 2" dia. stamped aluminum cap on 5/8" x 34" rebar in
place of found 1/2" bar

Wit: N15°E 33.63' to set N&T on W side 3" R. Pine
N41°E 37.60' to metal fence post
N53°W 58.53' to set N&T on SW side 14" W. Pine
N28°W 57.04' to set N&T on NE side 11" W. Pine
Center East-West gravel road 3' North
Set Blue Carsonite Post 33' North

Signed by:

Carl T. Kiiskila

Date:

8-15-12

Surveyor's Michigan License No.:

33981

