

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:  
Ogemaw  
(County)

Located In

Corner Code #

1. Public Land Survey	T	_____	R	_____	_____
	T	_____	R	_____	_____
2. Property Controlling in Section	S	32	T	24N	R 2E 11
	S	32	T	24N	R 2E 15
3. Miscellaneous Property in Section	S	_____	T	_____	R _____
	S	_____	T	_____	R _____

Register of Deeds Stamp & File Number

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Carl T. Kiiskila, in a field survey on October 24, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

11- This corner position was not established during the original government survey.

15- This corner position was not established during the original government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

11- Established the Northwest corner of the Southeast quarter of the Southwest quarter of section 32 as per B.L.M. instructions for the subdivision of a section.

15- Established the Southwest corner of the Southeast quarter of the Southwest quarter of section 32 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

11- Set 5/8" X 32" rerod with P.S. cap #33981  
 Wit: 5" Maple S23°W 14.70'  
 W. Pine S44°E 34.10'  
 26" W. Pine S16°E 44.25'  
 4" Oak N30°W 64.65'  
 Blue Carsonite Post North 1'±

15- Set 5/8" X 32" rerod with P.S. cap #33981  
 Wit: 12" W. Pine N08°E 43.83'  
 8" J. Pine N36°E 48.64'  
 5" J. Pine S25°E 50.15'  
 14" R. Pine S60°W 76.86'  
 Blue Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

11/9/05

Surveyor's Michigan License No.:

33981

