

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON

(County)

Located in:

Corner Code #

1. Public Land Survey

T48N R41W

G - 1

T49N R41W

G - 13

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

SURVEY & REMONUMENTATION

MAR 08 2001

SECTION

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Section Corner common to Sections 3 & 4, T48N R41W, and
Sections 33 & 34, T49N R41W.

I, Earl W. Applekamp, in a field survey on May 09, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|---|----|---|---|----|---|----|---|----|---|----|---|
| 1 | | | | | | | | | | | | | |
| 2 | 6 | | 5 | | | 4 | | 3 | | 2 | | 1 | |
| 3 | | | | | | | | | | | | | |
| 4 | 7 | | 8 | | | 9 | | 10 | | 11 | | 12 | |
| 5 | | | | | | | | | | | | | |
| 6 | 18 | | 17 | | | 16 | | 15 | | 14 | | 13 | |
| 7 | | | | | | | | | | | | | |
| 8 | 19 | | 20 | | | 21 | | 22 | | 23 | | 24 | |
| 9 | | | | | | | | | | | | | |
| 10 | 30 | | 29 | | | 28 | | 27 | | 26 | | 25 | |
| 11 | | | | | | | | | | | | | |
| 12 | 31 | | 32 | | | 33 | | 34 | | 35 | | 36 | |
| 13 | | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established by Wells Burt, U.S. Deputy Surveyor, June 1851. Set Black Ash Post.

ORIGINAL BEARING TREES:

14" Hemlock N27°E 35 Links (23.10 feet)
12" Hemlock N67°W 46 Links (30.36 feet)

FEEK GROUP APPROVED

Earl W. Applekamp
COUNTY CLERK

5-24-00

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Near the calculated position I found remnants of an old fence running North. I was told by Reginald McDonald, a 74 year old resident, living near this corner, that this fence was used to fence leased land from a timber company for grazing cattle. Another fence which is visible, runs East & West along an erratic line. I re-established the corner by single proportionate measurement and on line between opposite Section corners.

Research on file with the Ontonagon County Remonumentation Program Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2½"X30" split base aluminum pipe with a 3" cap stamped to read: County Remonumentation, T48N, T49N, R41W, S3, S4, S33, S34, 2000, P.S. 17610. I established three bearing trees and a reference object.

Nail in 4" Spruce S53°W 57.65' - Nail in 7" Aspen S67°E 29.37'
Nail in 7" Aspen N86°W 38.90' - 6" Steel Sign Post, North 0.74'



Signed by

Earl W. Applekamp

Date May 22, 2000

Surveyor's Michigan License No. _____

17610