

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

SURVEY & REMONUMENTATION

MAR 02 2001

SECTION

Register of Deeds Stamp & File Number

For corners in
ONTONAGON
(County)

Located in: Corner Code #

1. Public Land Survey T48N R 41W G-2
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

$\frac{1}{4}$ Corner common to Sections 3 & 4, T48N R41W.

2000

I, Earl W. Applekamp, in a field survey on June 03, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5			4		3		2		1	
3													
4	7		8			9		10		11		12	
5													
6	18		17			16		15		14		13	
7													
8	19		20			21		22		23		24	
9													
10	30		29			28		27		26		25	
11													
12	31		32			33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established by Wells Burt, U.S. Deputy Surveyor, June 15, 1851. Set Wood Post.

ORIGINAL BEARING TREES:

10" Yellow Birch N70°W 8 Links (5.28 Feet)
10" Maple N38°E 6 Links (3.96 Feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original or subsequent evidence was found. Corner was re-re-established by single proportionate measure between opposite corners North and South. This position is in conformance with a call South 132 feet to a Stream.

Research on file with the Ontonagon County Remonumentation Program Representative.

DEED GROUP EXEMPTED

Earl W. Applekamp 6-21-00
COUNTY REMONUMENTATION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the Corner position I set a 2 $\frac{1}{2}$ "x30" split base aluminum pipe with a 3" cap stamped to read: County Remonumentation, T48N, R41W, $\frac{1}{4}$, S3, S4, 2000, P.S. 17610. I established three bearing trees and a reference object.

Nail in 6" Maple S64°W 51.32' - Nail in Twin 6" Elm S85°E 37.09'
Nail in 5" Maple N29°E 32.99' - 6' Steel Sign Post, North 0.59'



Signed by Earl W. Applekamp
Surveyor's Michigan License No. 17610

Date June 14, 2000