

JUDITH D. ROENH

1P

Ontonagon County

Page 1 of 1

LC 5/280

JEN Date 05/30/2000

Time 15:10:50

RECORDING FEE:

9.00

# LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

## SURVEY & REMONUMENTATION

MAR 02 2001

SECTION

Register of Deeds Stamp &amp; File Number

For corners in

ONTONAGON

(County)

Located In:

Corner Code #

1. Public Land Survey

T48N R 41W

G - 3

2. Property Controlling  
in Section

S

T

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Section Corner common to Sections 3, 4, 9 &amp; 10, T48N R41W.

I, Earl W. Applekamp, in a field survey on May 10, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established by Wells Burt, U.S. Deputy Surveyor, June 15, 1851. Set Wood Post.

ORIGINAL BEARING TREES:

30" White Pine S70°W 23 Links (15.18 feet)  
12" Aspen N11°W 7 Links (4.62 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original or subsequent evidence was found. Corner was re-established by double proportionate measurement from the SE Corner of Section 5 West, the South  $\frac{1}{4}$  Corner of Section 2 East, the NE Corner of Section 4 and the SE Corner of Section 9 South.

Research on file with the Ontonagon County Remonumentation Program Representative.

DEED GROUP APPROVED

Earl W. Applekamp 5-24-00  
COUNTY CLERK

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a  $2\frac{1}{2}$ "x30" split base aluminum pipe with a 3" cap stamped to read: County Remonumentation, T48N R41W, S3, S4, S9, S10, 2000, P.S. 17610. I established three bearing trees and a reference object.

Nail in Twin 9" Maple S17°W 74.18' - Nail in 9" Maple S81°E 63.28'  
Nail in 5" Maple N38°E 46.48' - 6' Steel Sign Post, West 0.64'



Signed by

Earl W. Applekamp

Date May 22, 2000

Surveyor's Michigan License No.

17610