

JUDITH D. ROEHM

1P

Ontonagon County

Page 1 of 1

LC 5/281

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

DATE: 05/30/2000

Time 15:11:11

RECORDING FEE:

9.00

For corners in

ONTONAGON

(County)

Located in:

Corner Code #

1. Public Land Survey

T48N R41W

I - 1

T49N R41W

I - 13

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

SURVEY &
REMONUMENTATION

MAR 02 2001

SECTION

Register of Deeds Stamp & File Number

4. Lot No. _____ Recorded Plat _____

5. Private Claims _____

Section Corner common to Sections 2 & 3, T48N R41W and
Sections 34 & 35, 49N R41W.

I, Earl W. Applekamp, in a field survey on May 05, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

| | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|----|---|----|---|----|---|----|---|----|---|----|---|---|
| 1 | | | | | | | | | | | | | |
| 2 | 6 | | 5 | | 4 | | 3 | | 2 | | 1 | | |
| 3 | | | | | | | | | | | | | |
| 4 | 7 | | 8 | | 9 | | 10 | | 11 | | 12 | | |
| 5 | | | | | | | | | | | | | |
| 6 | 16 | | 17 | | 18 | | 19 | | 20 | | 21 | | |
| 7 | | | | | | | | | | | | | |
| 8 | 19 | | 20 | | 21 | | 22 | | 23 | | 24 | | |
| 9 | | | | | | | | | | | | | |
| 10 | 30 | | 29 | | 28 | | 27 | | 26 | | 25 | | |
| 11 | | | | | | | | | | | | | |
| 12 | 31 | | 32 | | 33 | | 34 | | 35 | | 36 | | |
| 13 | | | | | | | | | | | | | |

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established by Wells Burt, U.S. Deputy Surveyor, June 1851. Set Hemlock Post.

ORIGINAL BEARING TREES:

36" White Pine N70°E 19 Links (12.54 feet)
16" Cedar N75°W 10 Links (6.60 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner was found. Near the calculated corner position there was a fence running North & South and East. This fence has been in place for many years and is currently being used to contain cattle. I accepted this position as the only logical position for the corner and monumented it as shown below.

Research on file with the Ontonagon County Remonumentation Program Representative.

FREE GROUP APPROVAL

Earl W. Applekamp 5-24-00

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 1/2" x 30" split base aluminum pipe with a 3" cap stamped to read: County Remonumentation, T48N, T49N, R41W, S2, S3, S34, S35, 2000, P.S. 17610. I established three bearing trees and a reference object.

Nail in 5" Aspen S24°W 69.63' - Nail in 5" Aspen N89°E 55.53'
Nail in 6" Maple N34°W 141.13' - 6' Steel Sign Post, West 0.88'

Signed by Earl W. ApplekampDate May 22, 2000Surveyor's Michigan License No. 17610