

# SURVEY & REMONUMENTATION

MAR 02 2001

SECTION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970.

For corners in

ONTONAGON

(County)

Located in:

Corner Code #

1. Public Land Survey

T48N R41W

T49N R41W

T R

T R

S T R

S T R

S T R

S T R

2. Property Controlling in Section

3. Miscellaneous

Property in Sec.

4. Lot No. Recorded Plat

5. Private Claims

1/4 Corner common to Sections 1 & 36, T48N T49N, R41W.

2000

I, Earl W. Applekamp, in a field survey on Nov. 10, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by William A. Burt, U.S. Deputy Surveyor, summer of 1847. Set Cedar Post.

ORIGINAL BEARING TREES:

14" Cedar

5" Cedar

N05°E  
N67°W

3 Links (1.98 Feet)  
16 Links (10.56 Feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Corner was re-established on line and equal distance between opposite Section Corners, East and West.

Research on file with the Ontonagon County Remonumentation Program Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 1/2" X 30" split base aluminum pipe with a 3" Cap stamped to read: County Remonumentation, T48N, T49N, R41W, 1/4, S1, S36, 2000, P.S. 17610. I established 3 bearing trees and a reference object.

Nail in 8" Aspen N39°W 57.46' - Nail in 5" Balsam S85°E 88.99'  
Nail in 12" Aspen N57°E 65.10' - 6" Steel Sign Post, South 0.92'

Signed by

Surveyor's Michigan License No.

17610

Date November 24, 2000

JUDITH D. ROEHM

Ontonagon County

Page 1 of 1

JEM Date 12/07/2000

Time 14:41:39

RECORDING FEE:

1P

LC 5/351

9.00

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

