

SURVEY & REMONUMENTATION

MAR 02 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

ONTONAGON
(County)

Located in:

Corner Code #

1. Public Land Survey

T48N R40W

T49N R40W

T R

T R

T R

T R

T R

T R

C - 1
C - 13

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

JUDITH D. ROEHM

1P

Ontonagon County

Page 1 of 1

LC 5/349

JEM Date 12/07/2000

Time 14:41:12

RECORDING FEE:

9.00

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Section Corner common to Sections 5 & 6, T48N R40W
& Sections 31 & 32, T49N R40W.

I, Earl W. Applekamp, in a field survey on Nov. 09, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by John Burt, U.S. Deputy Surveyor, July 1847. Set Sugar Post.

ORIGINAL BEARING TREES:

12" Sugar

N16°E

37 Links (24.42 Feet)

10" Sugar

N37°W

10 Links (6.60 Feet)

DEED GROUP APPROVED

Earl W. Applekamp
COUNTY REGISTER

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Near the calculated position there was a blazed 16" Sugar Maple with two yellow tags. One dated 8-69, placed by U.S. Forest Personnel, indicating the corner was N38°W, 3.5 feet. The other was placed by Champion Inc. Personnel, dated 10-85, indicating corner is N60°W, 2 feet. A blue line was painted East & West from the stated corner position and timber cut to the line about 2 years ago. I established the corner at the above indicated position.

Research on file with the Ontonagon County Remonumentation Program Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 1/2"X30" split base aluminum pipe with a 3" Cap stamped to read: County Remonumentation, T48N, T49N, R40W, S5, S6, S31, S32, 2000, P.S. 17610. I established three bearing trees and a reference object.

Nail in 7" Sugar Maple N34°W 30.39' - Nail in 12" Sugar Maple S06°E 33.86'
Nail in 9" Sugar Maple N70°E 26.53' - 6' Steel Sign Post, North 1.53'



Signed by Earl W. Applekamp
Surveyor's Michigan License No. 17610

Date November 27, 2000