

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON
(County)

Located in:

Corner Code #

1. Public Land Survey

T48 R41
T49 R41
T R
T R
S T R
S T R
S T R
S T R

K-1
K-13

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

SURVEY &
REMONUMENTATION

MAR 02 2001

SECTION

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Section Corner common to Sections 1 & 2, T48N R41W &
Sections 35 & 36, T49N R41W.

I, Earl W. Applekamp, in a field survey on Sept. 21, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original Corner established by William A. Burt, U.S. Deputy Surveyor, summer of 1847. Set Cedar Post.

ORIGINAL BEARING TREES:

14" Cedar N25°E 21 Links (13.86 Feet)
14" Hemlock N44°W 15 Links (9.90 Feet)

YEAR GROUP APPROVED
Earl W. Applekamp
COUNTY REPRESENTATIVE
9-27-00

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Calculated Corner position falls in an old graded up road running North & South with some gravel, but now is grass covered. From the calculated position an old fence runs East and West with fields being farmed NE & SW from this position. I re-established the corner at the intersection of the center-line of the old road and the fence lines East & West as being the only logical position for the corner.

Research on file with the Ontonagon County Remonumentation Program Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 1/2"X30" split base aluminum pipe with a 3" cap flush with the top of the old road. Cap is stamped to read: County Remonumentation, T49N, T48N, R41W, S1, S2, S35, S36, 2000, P.S. 17610. I established 3 bearing trees and a reference object.

Nail in 8" Aspen N74°W 87.11' - Nail in 5" Aspen S10°E 135.75'
Nail in 6" Aspen N16°W 108.86' - 6' Steel Sign Post East 0.47'



Signed by Earl W. Applekamp
Surveyor's Michigan License No. 17610

Date September 25, 2000