

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
OSCEOLA

(County)

Located In:

Corner Code ##

1. Public Land Survey

T 19N R 9W

1-9

T      R     

1-10

T      R     

T      R     

2. Property Controlling  
in Section

S 26 T      R     

3

S 26 T      R     

10

3. Miscellaneous  
Property in Sec.

S      T      R     

S      T      R     

Register of Deeds Stamp & File Number

4. Lot No.         , Recorded Plat         

5. Private Claims         

I, CARL F. ROSER, in a field survey on 02/09, 19 88,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1-9

1-10

3

10

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1-9

1-10

3

10

FD OLD IR ROD IN 2 VIT TILES  
AS NOTED BY A. TEMPLE IN 1892.  
COR IS BURIED IN OLD N-S FN. &  
IN LINE W/FN BERN E; RAISED  
W/DNR MON. TEMPLE FD BOTH  
UGST'S, ONE DEAD & THE OTHER  
ONE DOWN. COR FITS 1 WIT FROM  
RECORDS AT N. MCCLUNG'S OFFICE,  
OLD POCKET FIELD NOTE BOOKS,  
DATES 1906 TO 1910.

FD CD SURVEYOR, A. TEMPLE'S IR  
ROD IN VIT TILE. FD BOTH  
TEMPLES 1892 PINE STP WITS  
THAT FIT COR GOOD. TEMPLE FD  
BOTH US BEECH BTS. OLD FN COR  
W/FN N&S IS 172' (+3') E &  
27' (+10') N.

ESTAB. NW COR, S1/2-NW1/4,  
SEC. 26 PER STD BLN  
INSTRUCTIONS. THERE ISN'T A  
DEFINITE FN COR.

ESTAB SW COR, NW 1/4-SW 1/4,  
SEC. 26 PER STD BLN  
INSTRUCTIONS. COR FALLS ON  
W'LY SLP OF HILL

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1-9

1-10

3

10

FD 1/2" IR ROD IN 2-3" X 12"  
TILES; ADDED DNR MON & CED  
POST.  
16" SOFT MAPLE S60°W 29.9'  
42" SOFT MAPLE N45°W 73.8'  
6" SOFT MAPLE N15°W 48.0'

FD OLD 1/2" X 48" IR IN 3"  
VIT. TILE; ADDED CED POST.  
16" TN. MAPLE N20°W 35.3'  
18" MAPLE IN IN  
CLUMP OF 3 N33°E 8.5'  
OLD E-W FN DUE N 27'

DROVE 5/8" X 34" RE-ROD W/RLS  
CAP & SET CED POST.  
5" SOFT MAPLE N40°W 31.4'  
12" R. OAK N25°E 45.5'  
3" SOFT MAPLE N60°E 38.4'  
4" SOFT MAPLE S05°W 4.8'  
OLD FN NLY DUE N 33'±3'  
OLD FN ELY DUE S 22'±3'

DROVE 5/8" X 34" RE-ROD W/RLS  
CAP & SET CED POST W/LOC TAG.  
6" MAPLE S55°E 25.1'  
3" TN. R. OAK S35°W 37.6'  
2" MAPLE S70°W 19.3'  
OLD N-S FN DUE E 230'±2'

Signed by Carl F. Roser 02-05-91 Date

Surveyor's Michigan License No. 12028

