LAND CORNER RECORDATION CERTIFICATE LIBER 3 Filing Requirement of Act 74, Mich. P.A. 1970

or comers in			PAGE 18
Oscoda (County)	Located In:	Corner Code :≠≠	FILED
Public Land Survey	7 27N R 1E	_C-13	At 11:20 o'clock A M
	Ţ R		Date June 6 10 90
	T R T R		PATRICIA WRIGHT
Property Controlling	\$ T R		Register of Deeds
in Section	S T R		Oscoda County, Michigan
Miscellaneous	S T R		Register of Deeds Stamp & File Number
Property in Sec.	S T R	L	· · · · · · · · · · · · · · · · · · ·


Norman C. Caldwell in a field survey on _ __March hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned lines 1 and 2 above were in conformance with regulations and rules therefore as required in the irrent manual of survey instructions of the United States Department of the Interior, Bureau of Land anagement or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 love were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a purt of Law; established, re-established, monumented, re-monumented, recovered, found as pressed below:

Private Claims

OTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

Post set by Clason, May 16&17, 1839. Spruce Pine 8" N61°W .96 (63.36') Spruce Pine 4" N22 1/2°E .50 (33.00')



Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(C-13) 6" conc. mon. w/brass cap placed by Guy R. Veal, Cadastral Engineer, 1937.

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(C-13) Standard Cor. 31&32, T27N-R1E

Fnd. U.S.G.L.O. conc. mon. @ E. edge plowed N-S drive. Accepted as a careful & faithful reestablishment of the position

of the original corner.

N30°W 98.9' 18" Oak (R) Carsonite Witness Post

East 34.2' closing cor. 5&6, 26/1 16" Oak (R)
N85°W 12.5' fe. cor. post
N45°E 49.7' P. Pole HINTE OF MICA

NORMAN C. CALDWELL

April 26, 1990

LAND

SURVEYOR¹⁰

REVISED JAN., 1983

rveyor's Michigan License No. .