

MAR 1 9 1997

•			:	:				
•		ER RECORDATION CERTIFI	CATE	: ;	,	,	0	
For corners in		rement of Act 74, Mich. P.A.	1970	Li	ber	4/	91	15
Oscoda (County)	Located in:	Corner Code # .		ļ	•	•	<i>'</i>	
•	-1	[į		PTATE 61		1111	
1. Public Land Survey	T _27N R _2E	M - 3		į	STATE OF	A COUNTY		
·	T 27N R 3E		1			FILED	٠.	
	<u>T</u> R							
2. Property Controlling	T R		:	. 2	6 NOV 90	3:15	P.M.	
in Section	S T R		j.		natev	4 5575	r.m	
3. Miscellaneous	STR		į		PAISI	J. PETE	KS roe	
Property in Section	S T R		Regist	er of De	REGISTE eds Sta	mp & Fi	le Nui	mber
•								
Lot No, Rec	orded Plat	<u> </u>	;	A B	C D E	F G	H: ≀) k
5. Private Claims	· · · · · · · · · · · · · · · · · · ·		 ;	2 5				ŢŢ
	•			3				
		•	- ;	4 7				
Marvin E. Myers in	a field survey onJun	ne 28 , 19 96	r,	5	ا	ا ا	Ĭ	"
 hereby certify that under require 	ments of P.A. 74, Michigan P.	A, of 1970, the corner points mention	ed 🖟	6-10-	17			
lines 1 and 2 above were in confo	ormance with regulations and r	rules therefore as required in the curre	ent 🏃	7		ï		
lanagement or by a decree of a C	Court of Law and/or that the co	nent of the Interior, Bureau of La orner points mentioned in lines 3, 4 a	nd (200			
above were in conformance with	h the rules of the Michigan Bo	pard of Professional Surveyors or by	/a /		1	-212	2	23
lecree of a Court of Law; establish s expressed below:	hed, re-established, monumen	ited, re-monumented, recovered, four		0 -30-	17			
1				1 1	29 	-282	(26
IOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.					72			
on unis ceruncate.				21				
			1	2 31 — 3 — —	32	33		لــــــــــــــــــــــــــــــــــــــ
Description of original mo	nument and accessories a	and/or subsequent restoration;	(1 (1	3 31	32	33 - 3		
Description of original mo ection corner common to So O Lewis Clason May 1839	Norm Galdwei	and/or subsequent restoration: 12E & Sections 6 & 7 I27N, R1 11 Apr. 28, 1971) 3E	2 31	32	1 3		Ĩ.l.
Description of original mo ection corner common to St O Lewis Clason May 1839 on(A)Set post T: (1) 30" Maple 832% 5	Norm Caldwe LCRC Liber (11 Apr. 28, 1971 2. page 395	19 (1 3E	2 31—3	32			Ĩ.
Description of original mo ection corner common to St O Lewis Clason May 1839 on(A)Set post II: (1) 30" Maple \$32½°W 5 (2)11" Beech N52½°W 51	LCRC Liber 1 1 lks. Mon.(B), (D) 1 lks. Co. Cor. (c)	ll Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe)	9 1 3E	2 31 3	32			Ĩ
Description of original moection corner common to St. D Lewis Clason May 1839 on(A)Set post II: (1) 30" Maple S325°W 51 (2)11" Beech N52½°W 51	LCRC Liber: Mon.(B), (D) Iks. Co. Cor. (c) WIT: (3), (4)	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5)	3E	2 31				Ĩ. l.
Description of original moection corner common to St. O Lewis Clason May 1839 on(A)Set post T: (1) 30" Maple S32½°W 51 (2)11" Beech N52½°W 51 orm Caldwell Date Unknown on(B)3/4" Bolt T: (3)12" Beech S68°E 11.	I lks. Mon. (B), (D) Co. Cor. (c) WIT: (3), (4) Larry Beaure	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992	3E	2 - 31 3				<u> </u>
Description of original moection corner common to St. D Lewis Clason May 1839 on(A)Set post [T: (1) 30" Maple S32½°W 51 (2)11" Beech N52½°W 52 Orm Caldwell Date Unknown on(B)3/4" Bolt T: (3)12" Beech S68°E 11. (4)6" Bass N12°E 6.6'	Norm Caldwe LCRC Liber 1; 11 lks. Mon.(B), (D) Co. Cor. (c: WIT: (3), (4 Larry Beaure Liber 192, [Mon(D)	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140	3E	2 31				<u> </u>
Description of original moection corner common to St. D Lewis Clason May 1839 on(A)Set post T: (1) 30" Maple \$32\frac{1}{2}\text{W} 51 Orm Caldwell Date Unknown on(B)3/4" Bolt T: (3)12" Beech \$68\text{E} 11. (4)6" Bass \$N12\text{E} 6.6" (5)7" Maple \$77\text{W} 10.3	Norm Caldwe LCRC Liber : 11 lks. Mon.(B), (D) Co. Cor. (c. WIT: (3), (4 Larry Beaure Liber 192, 1 Mon(D) WIT: (6)8" 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30°	9 3E	2 31 3				<u> </u>
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32½°W 51 (2)11" Beech N52½°W 51 orm Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass N12°E 6.6' (5)7" Maple \$77°W 10.3 canneth Ostling Nov. 1968	Norm Caldwe LCRC Liber : 1 lks. Mon.(B), (D) Co. Cor. (c: WIT: (3), (4 Larry Beaure 1 Liber 192, p Mon(D) WIT: (6)8" p (7)7" p	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' IW.Beech S65°E 11.94' Eim S40°W 4.19'	3E	2—31—3		3		
Description of original moection corner common to St. O Lewis Clason May 1839 on(A)Set post T: (1) 30" Maple S325 % 5 (2)11" Beech N52½ % 51 orm Caldwell Date Unknown on(B)3/4" Bolt T: (3)12" Beech S68 E 11. (4)6" Bass N12 E 6.6' (5)7" Maple S77 W 10.3 enneth Ostling Nov. 1968 on. (C)Fd. 5/8" iron bolt on. N-S road grade	Norm Caldwe LCRC Liber LCRC Liber LCRC Liber LCRC Liber LCRC LCRC	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' Tw. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80'		2-31-33-33		1 1		
Description of original molection corner common to St. Clason May 1839 on(A)Set post T: (1) 30" Maple \$32\formaller{1}{2}\text{w} 51 Orm Caldwell Date Unknown on(B)3/4" Bolt T: (3)12" Beech \$68°E 11. (4)6" Bass \$12°E 6.6' (5)7" Maple \$77°W 10.3 Conneth Ostling Nov. 1968 On(C)Fd. 5/8" iron bolt d. N-S road grade Description of comer evid	Norm Caldwe LCRC Liber 1 1 1 1 1 1 1 1 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' IW.Beech S65°E 11.94' Eim S40°W 4.19'		2-31313131313131313131		1 1		
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post T: (1) 30" Maple \$32\frac{1}{2}\text{W}\$ 51 C2)11" Beech N52\frac{1}{2}\text{W}\$ 52 orm Caldwell Date Unknown on(B)3/4" Bolt T: (3)12" Beech \$68\text{E}\$ 11. (4)6" Bass N12\text{E}\$ 6.6' (5)7" Maple \$77\text{W}\$ 10.3 canneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt d. N-S road grade Description of comer evid	Norm Caldwe LCRC Liber 1 1 1 1 1 1 1 1 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' Tw. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80'		2 31		1		
Description of original moection corner common to St. O Lewis Clason May 1839 on(A)Set post II: (1) 30" Maple S325°W 51 OFF Caldwell Date Unknown on(B)3/4" Bolt II: (3)12" Beech S68°E 11. (4)6" Bass N12°E 6.6' (5)7" Maple S77°W 10.3 Canneth Ostling Nov. 1968 on. (C)Fd. 5/8" iron bolt N-S road grade	Norm Caldwe LCRC Liber 1 1 1 1 1 1 1 1 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' Tw. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80'		2-31 3		1		
Description of original morection corner common to St. D Lewis Clason May 1839 on(A)Set post Cl. 130" Maple S32½ W 51 (2)11" Beech N52½ W 51 orm Caldwell Date Unknown on(B)3/4" Bolt Cl. (3)12" Beech S68°E 11. (4)6" Bass N12°E 6.6' (5)7" Maple S77°W 10.3 caneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt N-S road grade count of Comer evident (5) ound (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' Tw. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80'	ishing cor		rner	1		
Description of original morection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32\form Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass \$N12°E 6.6' (5)7" Maple \$77°W 10.3 onneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt (N-S road grade on Description of comer evident (5) ound (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' IW. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80' d applied in restoring or reestabl	ishing cor	nal co		1		Ĩ
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32½ % 51 (2)11" Beech \$52½ % 51 orm Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass \$12°E 6.6' (5)7" Maple \$77°W 10.3 caneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt of N-S road grade count of the count of the count (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' IW. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80' d applied in restoring or reestabl	ishing cor	nal co		60		Ĩ
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32½ % 51 (2)11" Beech \$52½ % 51 orm Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass \$12°E 6.6' (5)7" Maple \$77°W 10.3 caneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt of N-S road grade count of the count of the count (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' Tw. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80' d applied in restoring or reestable Lishment of the position of the	ishing cor	nal co		9 C		Ĩ
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32½ % 51 (2)11" Beech \$52½ % 51 orm Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass \$12°E 6.6' (5)7" Maple \$77°W 10.3 caneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt of N-S road grade count of the count of the count (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' IW. Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80' d applied in restoring or reestabl	ishing cor	nal co		96	3	Ĩ
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32½ % 51 (2)11" Beech \$52½ % 51 orm Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass \$12°E 6.6' (5)7" Maple \$77°W 10.3 caneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt of N-S road grade count of the count of the count (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' I'w.Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80' d applied in restoring or reestable Lishment of the position of	ishing cor	nal co				
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32½ % 51 (2)11" Beech \$52½ % 51 orm Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass \$12°E 6.6' (5)7" Maple \$77°W 10.3 caneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt of N-S road grade count of the count of the count (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' I'w.Beech S65°E 11.94' Eim S40°W 4.19' Maple East 18.80' d applied in restoring or reestable Lishment of the position of t	ishing cortice original the original three original	nal co		96		
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post T: (1) 30" Maple S32½ % 51 Orm Caldwell Date Unknown on(B)3/4" Bolt T: (3)12" Beech S68°E 11. (4)6" Bass N12'E 6.6' (5)7" Maple S77°W 10.3 Connecth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt AN-S road grade Description of comer evident (5) Cound (5) Cound (6) d is accepted as a careful	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' I'w.Beech S65°E 11.94' Elm S40°W 4.19' Maple East 18.80' d applied in restoring or reestable Lishment of the position of	ishing cortice original the original three original	nal co	rner	96		
Description of original molection corner common to St. O Lewis Clason May 1839 on(A)Set post (1) 30" Maple \$32½ % 51 (2)11" Beech \$52½ % 51 orm Caldwell Date Unknown on(B)3/4" Bolt (3)12" Beech \$68°E 11. (4)6" Bass \$12°E 6.6' (5)7" Maple \$77°W 10.3 caneth Ostling Nov. 1968 on(C)Fd. 5/8" iron bolt of N-S road grade count of the count of the count (5) ound (6)	Norm Caldwe LCRC Liber 1	11 Apr. 28, 1971 2, page 395)replaced with Std. ap & pipe) 4) & (5) egard Sept. 28, 1992 page 5140 Elm N30°E 7.30' I'w.Beech S65°E 11.94' Eim S40°W 4.19' Maple East 18.80' d applied in restoring or reestable Lishment of the position of t	ishing cortice original the original three original	nal co		96		

WIT: Nail W. side 8" Basswood (Elm) S40°W 4.19'
Nail W. side 4" Maple East 18.80'

1 (1); 1:

....

• • •

MITE OF MICHIGANIA MARVIN E MYERS PROFESSIONAL SURVEYOR No. 31000

Signed by. 31606 Surveyor's Michigan License No.

dan state Board of Priofessional Surveyors, Jan. 28, 1971 Revised May 14, 1975 Revised Jan., 1983