

1993

OSCODA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in **OSCODA**

Oscoda (County)	Located In:	Corner Code #
1. Public Land Survey	T 28N R 1E	A-1
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Liber 3 Pg 150

FILED

At 11:57 o'clock A.M.

Date 12-6 1993

Clerk/Register of Deeds
Oscoda County, Michigan
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Marvin E. Myers, in a field survey on DEC 3, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO - May 19, 1939 Hodgeson
Mon. - Post
WIT: 7" B.Oak N13°W 50 lks.
9" B.Oak S61½°E 64 lks.

Consumers Power Co. Mar. 1967
Mon. - Fd. ½" Bar
WIT: 10" N.Pine S65°E 105.60'
8" J.Pine N45°E 118.30'
24" Pine Stump S10°E 134.00'
Conc. Post SW 57.30'

Consumers Power Co. Oct. 1967
Mon. - 3/8" Pin
WIT: Blaze & Tag 12" Norway SE 105.55'
Blaze & Tag 12" Oak NW 103.58'
Blaze & Tag 8" J.Pine NE 118.15'
Cement Marker SW 57.33'

GLO - Dec. 1839 Clason
Mon. - as previously established
L.249, pg. 163 P.S. 18654
Mon. - 1" Bar
WIT: 20" N.Pine S65°E 105.60'
12" J.Pine N45°E 118.30'
24" Pine Stump N10°E 134.00'

1926 G. DeLamater
Mon. - Fd Post
WIT: 8" B. Oak N69°W 35.5
24" Y. Pine S10°E 134.0

Norman Caldwell 1968
Mon. - Fd. ½" Bar
24" Pine Stump S10°E 134.00'
8" J.Pine N45°E 118.30'
10" N.Pine S65°E 105.60'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found ½" bar and cap in Pav't box in centerline of Roads N-S- & E-W with Montmorency County Remonumentation cap on same
marked "PS 18654" and accepted as a perpetuation of the Original Government corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Mon- Standard Montmorency Monument in Pav't Box
Wit- US ARMY-WAR DEPT-CORP OF ENGINEERS BM concrete monument with Brass Cap stamped "B-3 1949" S64°E 122.05
Fd. Spike in SW face 15" Red Pine (Norway) S57°E 105.38
Fd. Spike in W. face 3" Red Pine (Norway) S23°W 119.25
Fd. Spike in SW face 8" Red Pine (Norway) N36°W 119.25



Signed by Marvin E. Myers

Date Dec 6, 1993

Surveyor's Michigan License No. 31600

Date approved Oct 25, 1993 Oscoda County Peer Group