

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Oscoda Located In Corner Code #
 (County)

1. Public Land Survey T 28N R 3E H-12
 T R
 2. Property Controlling S 34 T 28N R 3E 15
 in Section S T R
 3. Miscellaneous S T R
 Property in Section S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on June 19, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

H-12 Liber 3, Page 226 February 1980 Norman C. Caldwell R.L.S. #12018. Set the center of section 34 while doing a large retracement survey in the area.

15- Norman C. Caldwell R.L.S. #12018. Set the Southwest corner of the Southeast quarter of the Southwest quarter of section 34.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

H-12 Found a concrete monument as set by Norman C. Caldwell. 15- Found a 1/2" rod as set by Norman C. Caldwell.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-12 Concrete monument

Wit: 6" Maple S51°W 12.65'
 5" Maple N82°W 11.82'
 5" Maple N03°E 6.12'
 9" W. Birch S38°E 18.17'

15- Added P.S. cap #33981 to the found 1/2" rod

Wit: 9" Oak S51°W 10.54'
 8" Oak N40°W 14.39'
 14" R. Pine N64°E 19.19'
 8" Oak S59°E 6.30'

Signed by:

Carl T. Kiiskila

Date:

7-21-03

Surveyor's Michigan License No.:

33981

