

OTSEGO COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
South Charlton Township

For corners in

Otsego

(County)

Located In:

Corner Code #

1. Public Land Survey

T 29N R 1W

G-7

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, Carl T. Kiiskila, in a field survey on September 6, 2007 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-7 1856 GLO H. Mellen set post at corner of sections 15, 16, 21 & 22.

Wit: Y. Pine 8" N52°E 1.13

Sp. Pine 10" N29°W 2.53

1933 County Survey Book 2, Page 554, G. F. DeLaMater found one government B. plainly marked and P. Set 1 ½" gas pipe

Wit: S. Pine 8" N44°E 41.9'

S. Pine 6" S8°E 69.8'

S. Pine 6" N52°E 74.6'

1953 Department of Conservation Corner Record K. J. Ostling RLS #10068 found corner perpetuated by G. F. DeLaMater.

Wit: J. Pine 10" S2°E 20 links (13.2)

J. Pine 10" N87°W 60 links (39.6)

1991 Liber 3, Page 85, Larry G. Beauregard RLS #18654 found an existing 2 ½" pipe with a 1" pipe and DNR cap.

Wit: J. Pine 8" N10°E 60.85'

J. Pine 8" N45°E 61.07'

P. Pole N70°W 115.53'

15" Stump S02°E 13.20'

2004 Ronald Brand PS #43046 found DNR monument 80' East of centerline N-S road.

Wit: J. Pine 6" N09°E 37.87'

J. Pine 4" S79°E 24.70'

J. Pine 5" S01°W 26.50'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found a DNR monument fitting K. J. Ostling's witnesses and L. Beauregard's and R. Brand's survey in the area.

Wit: 13" J. Pine N17°E 60.85'

Notch in 14" J. Pine N42°E 60.85'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Accepted found DNR monument as a perpetuation of the original government corner location.

Wit: 13" J. Pine N17°E 60.85'

Notch in 14" J. Pine N42°E 60.85'

Set nail & tag 6" J. Pine S43°E 31.28'

Set nail & tag 7" J. Pine S26°W 57.44'

Center N-S gravel road West 80'

Signed by

Carl T. Kiiskila

Date

10/8/07

Surveyor's Michigan License No. 33981