

OTSEGO COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
South Charlton Township

For corners in

Otsego

(County)

Located In:

Corner Code #

1. Public Land Survey

T 29N R 1W

G-6

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, Carl T. Kiiskila, in a field survey on September 6, 2007 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-6 1856 GLO H. Mellen set quarter section post.

Wit: Sp Pine 10" S74°W 36

Sp. Pine 12" N25°W 47

County Survey Book 2, Page 554, 1933 G. F. DeLaMater shows a distance of 5285.0' for the West line of section 15.

County Survey Book 3, Page 474, Stanley Thorsen (1961) shows a distance of 2643.4' for the South half of the West line of section 15.

1991 Liber 3, Page 85, Larry G. Beauregard RLS #18654, found an existing ½" bar set by Stanley Thorsen (1965).

Wit: J. Pine 8" S20°W 8.18'

J. Pine 4" S03°W 9.82'

Poplar 15" N30°W 11.61'

J. Pine 5" N55°W 18.63'

Liber 1018, Pages 225 & 226, (2004) Certificate of Survey Ronald Brand PS #43046 found ½" iron 45' East of centerline.

Cherry 4" N70°E 3.91

R. Pine 6" S16°W 9.89'

R. Pine 8" S31°W 8.20'

Y. Birch 14" N20°W 11.71'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-6 Found a ½" x 48" bar fitting L. Beauregard's and Ronald Brand's witnesses in section 16.

5" Cherry N85°E 3.87'

8" J. Pine Stub S57°W 18.68'

10" J. Pine S34°W 8.20'

16" Poplar N20°W 11.70'

8" R. Pine Stub scribed S51°W 11.93'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-6 Set an Otsego County Monument in place of found ½" bar is accepted as careful and faithful re-establishment of the corner position.
Drove the ½" x 48" bar below grade on the East side of monument.

Wit: Set nail & tag 16" Poplar N20°W 11.48'

Set nail & tag 3" Maple S50°E 20.68'

Set nail & tag 4" Cherry S28°E 12.67'

Set nail & tag 10" J. Pine S34°W 8.20'

Found nail & tag 5" Cherry N85°E 3.81'

Centerline N-S road West 45'

Signed by

Carl T. Kiiskila

Date

10/9/07

Surveyor's Michigan License No. 33981

