

SURVEY &  
REMONUMENTATION

MAY 28 1997

COMMISSION

OTSEGO COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
ALSO Act 345, PA 1990

For corners in

OTSEGO (County)	Located in: Elmira Township	Corner Code #
1. Public Land Survey	T31N R4W	I-5
	T R	
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

OTSEGO COUNTY  
MICHIGAN  
RECEIVED FOR RECORD

96 DEC 30 PM 2:19

EVELYN H. PRATT  
CLERK / REGISTER OF DEEDS

Register of Deeds Stamp &amp; File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

I, Carl I. Robinson, in a field survey on December 14, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

## A. Description of original monument and accessories and/or subsequent restoration:

GLO 2/401: Austin Burt, 1850: Set Post-Beech 16" N 10°E 33 lks (21.8'), Sugar 12" S 52°W 28 lks (18.5').  
 CSR 1/12: J.M. Sanborn, 1881: Beech 16" N 10°E 33 lks (21.8'), Sugar 15" S 33½°E 19 lks (12.5').  
 CSR 1/57: A.W. Bates, 1891: Sugar 16" N 41°E 103 lks (68.0'), Sugar 8" S 55°E 85 2/3 lks (56.5').  
 CSR 2/464: G.F. DeLaMater, 1931: Found Stone with Bricks in Corner- Concrete Monument S 45°E 46.7', Concrete Monument N 45°W 46.7'.

LCRC 2/327: C.I. Robinson, 1986: Found 5/8" Iron Rod 8" deep & DeLaMater's Concrete Monument NW-Set Otsego County Monument-24" S. Maple N 72°E 79.20', GTE Terminal S 57°E 77.90', P. Pole S 50°W 55.67', Concrete Monument N 45°W 46.80'.

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Otsego County Monument on centerline of pavements east & south, DeLaMater's Concrete Monument northwest, and all my 1986 references.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Otsego County Monument on centerlines of pavements east & south, and is accepted as a careful and faithful perpetuation of the position of the original corner-spk 24" Maple N 72°E 78.94', Q Telephone Terminal S 57°E 77.65', spk P. Pole S 50°W 55.58', Concrete Monument N 45°W 46.80'.



## OTSEGO COUNTY REMONUMENTATION

Approved by the County Survey Peer  
Group, pursuant to Act 345, PA 1990.

DEC 15/96 David E. Sagan  
Date V. Chairman

Signed by Carl I. Robinson, PE & PS, Otsego County Surveyor  
Surveyor's Michigan License No. 16390

Date December 12, 1996