

DEC 01 1998

SECTION

OTTAWA COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
OTTAWA
(County)

Located In:

Corner Code #

1. Public Land Survey

T 7N R 15W M-7 (NE corner
Section 24)
Robinson Twp.

2. Property Controlling
in Section

S T R
S T R
S T R
S T R

3. Miscellaneous
Property in Sec.

RECORDED
98 SEP 29 PM 1:56

Randy Vugteveen
REGISTER OF DEEDS
OTTAWA COUNTY, MI

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Randal J. Vugteveen

I, _____, in a field survey on May 5, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

M-7 set by G.L.O. May 1832

Set Corner

18" Hemlock S72°W 8 links

10" Hemlock N29°W 32 links

Liber 2, Page 171

March 1973 (Spicer)

M-7 Iron Bolt

8" Sassafras N60°E 6.10'

24" Ash N50°W 18.84'

6" Sassafras N 17.4'

Iron S 51.5'

Gov. 56.1'

Liber 4, Page 63

April, 1980 Van Order

M-7 Cast Iron Monument

Centerline 33" Ash NW 19.77

Centerline 14" Sassafras NE 6.14'

Centerline 8" Sassafras East 9.44'

Centerline Buchanan Street South 27'+-

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M-7 Cast Iron Monument

Fd Nail & Tag SW side dead 32 ASH Az 313° 19.8'

Fd Nail & Tag E side 10" Sassafras Az = 0° 17.8'

Fd Nail & Tag NW side 16" Sassafras Az 48° 6.09'

Cast Iron Monument Allendale Cor Az 180° 51.64'

Accepted Cast Iron Monument as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-7 Cast Iron Monument

Nail and Ottawa County Remon tag South side 12" Poplar Az 282° 93.70'

Nail and Ottawa County Remon tag West side 14" Sassafras Az 15° 7.69'

Nail and Ottawa County Remon tag South side 10" Sassafras Az 108° 9.36'

Nail and Ottawa County Remon tag South side 10" Pine Az 102° 54.26'

Buchanan Street (Gravel) Az 180° 27'+-

Cast Iron Monument Az 180° 51.64'

Signed by

Randy Vugteveen

Date

July 23, 1998

Surveyor's Michigan License No.

28429

