

RECORDED

93 DEC 16 PM 1:00

OTTAWA COUNTY REMONUMENTATION  
**LAND CORNER RECORDATION CERTIFICATE**  
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Ottawa  
 (County)

Located In:

Corner Code #

1. Public Land Survey

T 7N R 16WK-12, E $\frac{1}{2}$  cornerT      R     

Section 35

T      R     T      R     2. Property Controlling  
in SectionS      T      R     S      T      R     3. Miscellaneous  
Property in Sec.S      T      R     S      T      R     

*Phyllis Dillman*  
 REGISTER OF DEEDS  
 OTTAWA COUNTY, MI

Register of Deeds Stamp &amp; File Number

4. Lot No.           , Recorded Plat           5. Private Claims           

I, THOMAS E. JOINER, in a field survey on 10-25-, 19 93,  
 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
 in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
 current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
 Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
 Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
 expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded  
 on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Railroad Rail Liber 4, Pg. 219

10" Red Pine N.E. 77.73  
 Power pole N.E. 86.15  
 16" Ash S. 20° E. 65.46  
 18" Maple West 55.75

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found cast iron monument and accepted as a careful and faithful perpetuation of the  
 position of the original corner.

8" Ash S.S.W. 54.94  
 24" Ash S.S.E. 66.46  
 12" Pine N.E. 47.38



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Cast Iron Monument

O.C. Remon tag & nail North side Power pole S. 62° E. 51.14  
 O.C. Remon tag & nail West side 18" Pine N. 30° E. 78.31  
 O.C. Remon tag & nail East side Power pole N. 34° W. 44.66  
 O.C. Remon tag & nail South side 24" Maple S. 89° W. 55.82

Signed by

*Thomas E. Joiner*  
 18435

Date

11-19-93

Surveyor's Michigan License No.