SURVEY & REMONUMENTATION

DEC 01 1998

OTTAWA COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

SECTION

Filing Requirement of Act 74, Mich. P.A. 1970

For	corners in					REC	ORDED	
	Ottawa (County)	Located in:		ner Code #		111	01112	
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	GRAND HA	ANEW TWO			98 JUL 2	4 PM Is	47
1.	Public Land Survey	T8N R16	SW G-8,	9	1			
		TR_		_	1	Light	Libella	, aut
		TR_ T R			1			i
2.	Property Controlling		SW Sout	th witness	1	OTTAY	TER OF DEEDS A COUNTY MI	
	in Section	S TR_		ument for G-8				
	Miscellaneous	S TR_		DOENTIAL	Registe	er of Deeds \$	Stamp & File	Number
	Property in Sec.	S T R	— (==	ENER#3		·		
4.	Lot No, F	Recorded Plat				A R C D	EFGH	1 J K L N
5. 1	Private Claims				1			
					2	6 5	4 3	12 1
					3	 	 	
	Steve Lampen	, in a requirements of P.A. 74,	field survey on Michigan B.A. of 107	lay 19 98		7 8	9 10	11 12
in lir	nes 1 and 2 above wer	e in conformance with re	egulations and rules	therefore as require	d in the		 	1-1-1-
		structions of the United Sof a Court of Law and/or				18 17	16 15	14 13
abov	ve were in conformance	with the rules of the Mich	nigan Board of Land	Surveyors or by a Dec	cree of a	19 20	21 22	1 72 74
	rt of Law; established essed-below:	l, re-established, monu	mented, re-monume	ented, recovered, for	und as 8	19 20	21 + 22	23 24
					10	30 29	28 27	26 25
NOT	TE: Not more than 4 on this certificat	corners, all in the sar	ne town and range	e, may be recorded	11		 	
	on this confincat	.			12	31 32	33 34	35 36
Α.	Description of origi	nal monument and acc					<u> </u>	
		ctions 21 and 22		section line betw hown on 1876 Monu				
-	36.00 Grand River and set M. post 1913 Monument Map by Peck; Plats of Corl's Addition - 1902, Grand View Addition - 1911							
		_						
	GLO - Mullet 183	7 n left bank Grand R		East & West $1/4$) on the Plat of				* *
	50.50 over to ma	rshy Island set pos	t Plat	No. 3 - 1937		15 OTTAN	ra Zachian	τV
		d and set on margin tions 15, 16, 21 and						
_				F			5-15-7	
В.	G-8 G-8 was n	er evidence found and ot monumented in th	e original GLO s	urveys.			9.11	
	Re-established t	he Section line bet	ween Sections 21	and 22 by finding		tion 1718 f	eet North o	of G-9 per
		p and extended Sect	,	_				
	Re-established to distance from G-	he North and South ; 7 to G-9.	position of the	GLO Meander post	at 36.00 ch	ains GLO me	asure by pr	coportionate
	coloristed the W	anth and Couth mad				14		يد شد
	monumentation at	orth and South posi the Northeast corn	er of Rycenga's	Assessor's Plat	c & west 1/4 as surveyed]	tine East by others.	rrom F-8 us	ing found
	Calculated the E	ast & West position	of G-8 on line	between the re-e	stablished G	LO Meander	post positi	on and G-7.
Calculated the East & West position of G-8 on line between the re-established GLO Meander post position Set Ottawa County Remonumentation iron and cap on the Section line between Sections 21 and 22 as a refer monument. This corner not monumented by the GLO surveys.								
								presence
	Calculated posit	ion of G-8 is accep	ted as the best	nosition of the	corner.			
				posicion or 5110 .	0011101			
	See sketch on ba	ck.				mill	unam _n ,	
C.	Description of mon	ument for corner and	accessories establ	ished to perpetuate	locating the	position of the	5 colerer 4.	
	G-8 Reference Mo	nument Ottawa Coun	ty Remonumentati	on iron and cap				as 21 & 22
	Southwesterly ban Hydrant, top cen		1° 14' 199° 46'	30 ± 56.24		ON SERVICE SURFINE SUR	MOEN :	, =
	_	te block building	298° 20'	328.95			AND	=
	Well casing, fac		311° 24'	93.46		En: Sun	VEYOR	
	Well casing, fac Well casing, fac		319° 45' 131° 35'	40.38 12.85		E 95: 3	7279	
	G-9		181° 14'	2376.22		My Chi.		e de la
	GLO meander post	position	1° 14'	28.90		Million F	AND Summ	\$11.00 (Receirt
Sia-	ied by Steven	\mathcal{P}_{-} .		Data	1	711111 2	mum, S	舞器
		- sampen		Date	JULY 2	20, 1995	>	#500 1500 1500 1500 1500 1500 1500 1500
Surv	∕eγor's Michigan Lice	nse No. <u>372</u>	77		FORM APPROVED I	Y MICHIGAN STATE	BOARD OF LAND SUR	VEYORS, JAN. 28, 197

