

APR 25 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON

(County)

Located in:

Corner Code =#

Recorded April 12 1994
at 1:10 o'clock P M. in
Liber 3 page 193
Judith K. Boehm
Register of Deeds

1. Public Land Survey T R
T R
T R
T R
2. Property Controlling S 9 T 46N R 39W #2
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

East 1/16 Corner, Sections 4, 9; T46N., R39W.

I, Richard L. Drahn, in a field survey on August 11, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Not established in original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Established corner by single proportion measure on line between the N.E. Section and the North 1/4 corner of Section 9.

PEER GROUP

Approved

Earl W. Applekamp 4-07-94
Ont Co, Rep.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a standard 2" diameter by 30" long split base aluminum monument with a 3 1/4" aluminum cap stamped to read: T46N., R39W.; E 1/16; S. 4, S. 9; 1993; R.L.S. 21564: from which I established the following new blazed and scribed bearing trees and/or reference objects:

14"	Spruce	N.86°W.	12.83 feet
8"	White Birch	N.19°E.	14.51 feet
6"	Aspen	N.78°E.	35.11 feet

A 6' steel sign post bears: S.48°W. 0.86 feet

Signed by Richard L. Drahn Date February 10, 1994

Surveyor's Michigan License No. 21564
U.S.F.S. E-12