

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON
(County)

Located In:

Corner Code #

1. Public Land Survey

T48N R39W

K-8

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Quarter Corner common to Sections 23 & 24, T48N R39W.

I, Earl W. Applekamp, in a field survey on June 13, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Artemas Curtis, U.S. Deputy Surveyor, September 20, 1851. Set Wood Post.

ORIGINAL BEARING TREES:

7" Yellow Birch N53°W 2.64 feet
7" Maple S74°E 16.50 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Corner falls in a County gravel road. Corner was re-established by single proportionate measure between opposite Section Corners and in the center-line of the gravel road.

Research on file with the Ontonagon County Remonumentation Program Representative.

PEER GROUP APPROVED

Earl W. Applekamp
COUNTY REPRESENTATIVE
7-15-97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 5/8"x12" rebar with a stamped cap 6" below top of gravel. I established a reference monument, a 2 1/2"x30" aluminum pipe with a cap stamped to read: County Remonumentation, T48N R39W, R.M., 1/4, S23, S24, 1997, P.S. 17610. I also established 3 bearing trees.

REF. MON. S54°E 59.45' - 14" White Pine N43°E 56.71'
23" White Pine N15°W 177.38' - 12" Scotch Pine N74°E 49.06'



Signed by Earl W. Applekamp
Surveyor's Michigan License No. 17610

Date June 14, 1997