

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ONTONAGON (County)	Located in:	Corner Code #
1. Public Land Survey	T 48NR 41W	B-9
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

REMONUMENTATION

OCT 8 1997

COMMISSIONER

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

$\frac{1}{4}$ Corner common to Sections 19 & 30, T48N R41W.

I, Earl W. Applekamp, in a field survey on August 22, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Wells Burt, U.S. Deputy Surveyor, June 12, 1851. Set Wood Post.

ORIGINAL BEARING TREES:

10" Cedar	N10°E	13.20 feet
12" Cedar	N80°E	13.20 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Corner was re-established by single proportionate measure between opposite section corners East & West.

Research on file with the Ontonagon County Remonumentation Program Representative.

DEED GROUP APPROVED

Earl W. Applekamp
COUNTY REPRESENTATIVE

9-17-97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 $\frac{1}{2}$ "X30" aluminum pipe with a 3" cap stamped to read: County Remonumentation, T48N R41W, $\frac{1}{4}$, S19, S30, 1997, P.S. 17610. I established 3 bearing trees and a reference object.

6" Aspen	S76°W	33.57'	-	4" Spruce	S20°E	37.63'
6 $\frac{1}{2}$ " Aspen	N15°E	29.05'	-	Steel Sign Post, East		1.25'



Signed by Earl W. Applekamp
Surveyor's Michigan License No. 17610

Date September 8, 1997