

SURVEY & REMONUMENTATION

APR 26 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
ONTONAGON
(County)

Located In:

Corner Code ~~44~~

1. Public Land Survey

T 48 R 42
T 49N R 42W

H-1
H-13 ✓

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

Recorded December 19, 1994
at 2:30 o'clock P. M. in
Liber Survey 3 page 248
J. W. Applekamp
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

1/4 Corner, S.3 & 34, T48, T49N R42W

I, Earl W. Applekamp, in a field survey on December 10, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by John Burt, U.S. Deputy Surveyor, August 1848. Set Sugar Maple Post.

Original Bearing Trees:

Sugar	12"	N19°W	15 Links	(9.90 feet)
Lynn	14"	N38°E	45 Links	(29.70 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence found. Highway M-28 has obliterated all original evidence. Corner was reset by single proportionate measurement on line between the NW & NE Corner of Section 3.

Research on file with the County Remonumentation Program Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a PK NAIL in the blacktop surface of Highway M-28. I set two reference monuments, one North and one South which are 2 1/4"x30" aluminum pipes with a 3 1/4" cap stamped to read: County Remonumentation R.M., 1/4, S.3, S.34, T48 T49N, R42W, 1994, P.S. 17610. These two monuments and 1/4 corner are on line. The following reference monuments and objects were used to tie in the corner.

Reference Monument North	52.12 Feet	-	3' Black Ash	S07°E	62.34 Feet
Reference Monument South	52.09 Feet	-	8" Maple	N23°W	75.43 Feet

ONTONAGON COUNTY
PEER APPROVED

Earl W. Applekamp
Snt to Rep
12-15-94



Signed by Earl W. Applekamp

Date December 13, 1994

Surveyor's Michigan License No. 17610