

# LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: June 1 2016

For corner(s) in: Ontonagon County

## Original Public Land Survey Corner

## Corner Code

S          T          R           
S          T          R           
S          T          R           
S          T          R         

## Property Corner

## 1/16 Corner Code

a. S 36 T 51N R 38W  
S          T          R           
b. S 36 T 51N R 38W  
S          T          R         

NE-NW 1/64 cor.

(GCDB 630170)

SW-NW 1/64 cor.

(GCDB 610150)

|    | A  | B | C | D  | E | F  | G | H  | I | J  | K | L  | M |    |
|----|----|---|---|----|---|----|---|----|---|----|---|----|---|----|
| 1  |    |   |   |    |   |    |   |    |   |    |   |    |   | 1  |
| 2  | 6  |   |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   | 2  |
| 3  |    |   |   |    |   |    |   |    |   |    |   |    |   | 3  |
| 4  | 7  |   |   | 8  |   | 9  |   | 10 |   | 11 |   | 12 |   | 4  |
| 5  |    |   |   |    |   |    |   |    |   |    |   |    |   | 5  |
| 6  | 18 |   |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |   | 6  |
| 7  |    |   |   |    |   |    |   |    |   |    |   |    |   | 7  |
| 8  | 19 |   |   | 20 |   | 21 |   | 22 |   | 23 |   | 24 |   | 8  |
| 9  |    |   |   |    |   |    |   |    |   |    |   |    |   | 9  |
| 10 | 30 |   |   | 29 |   | 28 |   | 27 |   | 26 |   | 25 |   | 10 |
| 11 |    |   |   |    |   |    |   |    |   |    |   |    |   | 11 |
| 12 | 31 |   |   | 32 |   | 33 |   | 34 |   | 35 |   | 36 |   | 12 |
| 13 |    |   |   |    |   |    |   |    |   |    |   |    |   | 13 |
|    | A  | B | C | D  | E | F  | G | H  | I | J  | K | L  | M |    |

## Part A. Corner History

a.) NE-NW 1/64 corner, being the SW corner of the NE 1/4 of the NE 1/4 of the NW 1/4 of Section 36. Not previously monumented.

b.) SW-NW 1/64 corner, being the NE corner of the SW 1/4 of the SW 1/4 of the NW 1/4 of Section 36. Not previously monumented.

## Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Established the position for the corner at the intersection of 1/64 lines.

b.) Established the position for the corner at the intersection of 1/64 lines.

## Part C: Field Evidence of Perpetuation or Monumentation of Corner

(a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
15" Spruce S83°E 12.15' mrkd "1/64S BT"  
7" Sugar S59°E 30.55' do  
4" Sugar S11°E 29.45' do  
4" Oak S52°W 28.65' do  
Set sq'd cedar post adjacent.  
E= 7841704.462 N= 223717.726

(b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
9" Balsam N45°E 11.25' mrkd "1/64S BT"  
8" Balsam S63°E 9.4' do  
4" Sugar S29°W 8.3' do  
7" Balsam N22°W 4.6' do  
Set sq'd cedar post adjacent.  
E= 7841300.850 N= 223330.617

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meters.  
Coordinate Reference: NGS PID DL6162, E= 7824690.922 m. N= 233745.718 m.

Stephan J. Szyszkoski

09/08/2016

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

