

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Ontonagon (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 35 T 51N R 40W S 26 T 51N R 40W S _____ T _____ R _____	1 8 _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 1 07/11/2011 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(1-Sec. 35) West 1/16 corner between Sections 26 and 35. Not established in the original survey.

(8-Sec. 26) West 1/16 corner, Section 26. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(1-Sec. 35) Established the corner midway and on the Section line between Section corner 1291.95'
west and Quarter corner 1291.95' east.

(8-Sec. 26) Established the corner midway and on a straight line between Quarter corner 1294.04' west
and Center of Section 26 1294.04' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(1) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
14" Maple S30E 5.1' mrkd "1/16S BT"
7" Sugar S32W 48.1' do
5" Sugar N27W 16.4' do
7" Sugar N09W 14.95' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

(8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Sugar N87E 11.9' mrkd "1/16S BT"
3" Oak S32E 8.0' do
6" Sugar S16W 24.6' do
5" W.Ash S50W 18.15' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 08/11/2011

For the Michigan Department of Natural Resources, Forest Management Division

