

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
Ontonagon  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 51N R 42W

T 51N R 41W

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Section

S T R

4. Lot No. , Recorded Plat

5. Private Claims

SURVEY &  
REMONUMENTATION

MAY 22 1997

COMMISSION

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

The section corner common to Sections 12, 13, 7, 18, T51N-R42W-R41W.

I, John R. Garske, in a field survey on July 23, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- In 1845, Austin Burt, U.S. Deputy Surveyor, set a post with the following bearing trees:  
8" Birch - S62°W - 35 links  
10" DO - N34°W - 18 links.
- 1966± Era MDOT Plans show corner 7.39 feet west of the curved centerline of Highway 64.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found a 3/4" diameter iron rod in an M.D.O.T. Monument Box which matches the location shown on the highway plans. The corner location matches stationing shown and our distances to corners with the plans. This corner has been used and accepted in many surveys of record, including a 1981 survey by William Immich, R.L.S.

Record research on file.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I established the following reference objects:

- 2 1/2" aluminum pipe with 3 1/4" aluminum cap stamped: T51N, R42W, R41W, R.M., S-12, S-7, S-13, S-18, 1996, R.L.S. 28410, N51°E, 53.76 feet with a steel sign rail 1.09 feet away.
- Another cap stamped the same as above except S55°E - 50.50 feet with a steel sign rail 1.31 feet away.
- Power Pole - S54°E - 77.79 feet

PEER GROUP APPROVED

Earl W. Applekamp  
COUNTY REPRESENTATIVE

8-14-96

SEE SKETCH ON BACK

Signed by

John R. Garske

Date

8-11-96

Surveyor's Michigan License No. 28410

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983