

**SURVEY &
REMONUMENTATION**

APR 29 1996

COMMISSION

JUDITH D. ROEHM
Ontonagon County
LC 3/ 401 JEM Fee: 9.00
Page 1 of 1

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Ontonagon Located In: Corner Code #
(County)

1. Public Land Survey	T	<u>52N</u>	R	<u>39W</u>	<u>F-11</u>
	T		R		
	T		R		
	T		R		
2. Property Controlling	S		T		
in Section	S		T		
3. Miscellaneous	S		T		
Property in Section	S		T		

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Joseph C. Domitrovich, in a field survey on October 25, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1/4 Corner Sections 28 & 33, T52N, R39W

1845- William A. Burt, set sugar 1/4 post

16" Lynn	N53°E	45 links
22" Lynn	N18°W	36 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Original corner and accessories have been destroyed by road construction and extensive farming.

East-West Firesteel road now runs over corner location. Re-established corner by single proportionate measurement. Corner works well with centerline of road and distant north-south fenceline to north.

Research on file with County Remonumentation Representative.

PEER GROUP APPROVED

COUNTY REPRESENTATIVE 11-06-95

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 5/8" rerod with a 3" diameter stamped aluminum cap and falls 1' north of centerline Firesteel Road.

Witnesses:

Power Pole	N66°E	72.68'	
3" Ironwood	S30°E	36.79'	
Reference Monument (Aluminum pipe with stamped cap)	South	26.94'	
Steel Sign Post	South	27.48'	
5" Balsam	S49°W	42.24'	

NOTE: Bearings are magnetic. Distances are to nail in side of witness objects unless noted.

Signed by J. C. Domitrovich

Date 11/05/95

Surveyor's Michigan License No. 37273

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

