

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Presque Isle

(County)

Located In

Corner Code #

1. Public Land Survey

T 33N R 2E I-9  
T 33N R 2E J-9

2. Property Controlling  
in Section

S T R  
S T R

3. Miscellaneous  
Property in Section

S T R  
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 29, 2008 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

I-9 G.L.O. 1851 Geo. H. Cannon set pine post for corner of sections 22,23,26 & 27

Wits: Spruce Pine 5" N54°W 15 links  
Spruce Pine 10" S39°E 24 links

J-9 G.L.O. 1851 Geo. H. Cannon

Wits: Y. Pine 18" N24°W 37 links  
Y. Pine 14" S08°E 30 links

Marcus Schaaf R.L.S. #3104 index shows he set a monument for the corner while working in the area CIRCA 1940 no witnesses given.

Marcus Schaaf R.L.S. #3104 index shows he set a monument for the corner while working in the area CIRCA 1940 no witnesses given.

Liber 314, Page 14, 1995 Norman Quaine P.S.#33984 found

A 2" pipe at old fence corner and at fire lane intersection.

Wits: N14°W 32.36' 6" R. Pine  
S52°E 33.44' 10" J. Pine  
S34°W 38.92' 11" Oak  
N62°W 15.97' 7" R. Pine

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

I-9 Found 2 1/4" pipe

J-9 Found 2 1/4" pipe

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-9 Set 1/2" X18" rod with PS Cap#33981 in found 2 1/4" pipe

Wit: Set nail and tag in East side of a 7" Red Pine N14°W 32.35'  
Set nail and tag in North side of a 6" R. Pine N62°W 16.00'  
Set nail and tag in East side of a 8" Oak S30°W 38.87'  
Set nail and tag in South side of a 10" J. Pine S54°E 33.38'  
Set carsonite post North 1'±

J-9 Set 1/2" X18" rod with PS Cap#33981 in found 2 1/4" pipe

Wit: Set nail and tag in NE side of a 8" R. Pine N48°W 30.62'  
Set nail and tag in Northeast side of a 6" R. Pine N25°W 35.31'  
Set nail and tag in West side of a 8" Jack Pine N12°E 43.00'  
Set nail and tag in South side of a 10" Red Pine S55°E 46.99'  
Set Carsonite post North 20'±

Signed by:

Carl T Kiiskila

Date:

9-15-08

Surveyor's Michigan License No.:

33981

