

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Presque Isle
(County)

Located In

Corner Code #

1. Public Land Survey	T	33N	R	4E	E-7
	T		R		
2. Property Controlling in Section	S	20	T	33N	R
	S		T		R
3. Miscellaneous Property in Section	S		T		R
	S		T		R

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on April 9, 2002 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

E-7 G.L.O. Alfred Millerd 1855 set section post

Wit: Yellow Pine 10 N28°W 15 links

Yellow Pine 10 S58°E 4 links

2- Ronald R. Bischer P.S. #22428 set a 1/2" rod for corner
no date or witnesses given.

Page 727 Presque Isle County Land Corner Records
October 1985 Delmer E. Porter P.S. #15410 set 1/2" rod
with P.S. cap from G.L.O. witnesses stump N28°W 9.9'
O.B.T. stump.

Wit: N68°W 34.10' 10" N. Pine

S43°W 23.53' 6" Maple

S17°E 16.63' 8" N. Pine

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

E-7 Found 1/2" Porter capped iron P.S. #15410.

2- Found 1/2" Bischer capped iron P.S. #22428.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-7 Found 1/2" capped rod (P.S. #15410), placed
1" X 48" pipe with P.S. cap #33981 over top.

Wit: 6" Red Pine N16°E 73.71'

8" White Pine N37°W 12.17'

7" White Pine S57°E 80.19'

7" White Pine S51°W 47.03'

Carsonite Post North 1'±

2- Found 1/2" rod with P.S. cap #22428

Wit: 13" Oak S84°E 53.40'

9" Maple S07°E 69.92'

9" Red Pine S88°W 54.50'

6" Jack Pine N07°E 74.71'

Carsonite Post North 1'±

Signed by:

Carl T. Kiiskila

Date:

8-26-02

Surveyor's Michigan License No.:

33981

