

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Presque Isle
(County)

Located In

Corner Code #

1. Public Land Survey T 33N R 8E J-9
T
2. Property Controlling in Section S 26 T 33N R 8E 2
S
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on January 19, 2000 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

J-9 Josiah Knauer D.S. July 1855
Set Quarter Section Post
Wit: 6" Tamarack S04°W 10 Links
6" Tamarack S23°W 6 Links

2- This corner position was not established during the original government survey.

Earl T. Lewis P.S. #27452 set a 1/2" rod for the North 1/4 corner of section 26.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

J-9 Found and accepted a 1/2" rod with P.S. cap #27452

2- Established the Northwest corner of the Northeast quarter of the Northeast quarter of section 26 as per BLM instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-9 1/2" rod with P.S. cap #27452
Wit: 5" Spruce S18°E 26.05'
4" Balsam S59°W 11.65'
3" Spruce S88°E 21.46'
3" Balsam N34°W 11.12'

2- Set 5/8" X 32" Rerod with P.S. cap #33981
Wit: 10" Ash West 15.99'
8" Cedar S43°W 8.03'
3" Balsam S22°E 8.05'
4" Balsam N61°E 4.10'
1/2" Rerod with P.S. cap S82°W 3.07'

Signed by:

Carl T. Kiiskila

Date:

10-21-03

Surveyor's Michigan License No.:

33981

