LIBER 334 PAGE 922

PRESQUE ISLE COUNTY 1999 PRESQUE ISLE COUNTY, STATE OF MICHIGAN REMONUMENTATIONECONDED

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 Personna Table. Located in: Corner Code # Content 1. Public Land Survey T. A. R		-	•	
Program Tells. Located in: Comer Code # SEGISTER OF DEEDS 1. Public Land Survey T. R				TFICATE
Preside Table 1. Public Land Survey T. R. T. R	For corners in	Filing Requir	ement of Act 74, Mich. P.	
2. Property Controlling S T R R S Needlaneous S T R R R S Needlaneous S T R R R R S Needlaneous S T R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R R S Needlaneous S T R R R R S Needlaneous S Needlaneous S T R R R R S Needlaneous S	-	Located In: Corr	ner Code#	
A. Lot No	1. Public Land Survey		A-4	
Register of Deeds Stamp & File Numb 4. Lof No		TR S TR S TR		DEC 2 9 1999
4. Lot No	3. Miscellaneous	S TR S TR		
I. Del mer. F. Porter in a field survey on Nov. 10 19 99 on hereby state that under recisioned for PA. A. Medium PA. of 1970; the corner points meritional for regulations are unsultable for the linked States Department of the Interior, Survey or United States Department of the Interior, Survey or were in conformance with regulations are unsultable for the Interior, Survey or Survey or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as persected between the Common with the native of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed between conformance with the native of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed between conformance with the native of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented. A. Description of original monument and accessories and/or subsequent restoration: A.4 GLO Notes — 1855 Sp. Pine 6" S22° W 26 Lks Fd Co. Mon Cap Sp. Pine 6" N13° W 28 Lks Fd Co. Mon Cap Sp. Pine 6" N13° W 28 Lks Fd Co. Mon Cap Sp. Pine 6" N13° W 28 Lks Fd Co. Mon Cap 10" Red Pine S40° E 26.98' 10" Red Pine S40° E 26.98' 10" Red Pine S40° E 28.85' B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: A-4 Found 4" Conc Mon/Brass Cap in Place N77° E 28.87' 14" Red Pine S49° W 49' Stump/Face Blaze C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: A-4 4" Conc Mon/Brass Cap S40° W 33.93' 14" Norway N34° W 61.78' 11" Norway N35° E 26.78' 15" Red Pine *Witness tags & nails used.	4 Let No Boord	fod Blot		
I. Delmer E. Porter in a feld survey on Nov. 10.19.99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in June 1970, the corner points mentioned on lines 1 and 2 above were in Charles of the International States Department of the Interior, Busines at required in the current manual of survey instructions of the United States Department of the Interior, Busines at a required in the current manual of survey instructions of the United States Department of the Interior, Busines at a second of 1 and Surveyors or by a Decree of a Court of Law, established, re-established, monumented, and the corrected on this certificate. NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: A4 GLO Notes - 1855 Set 1/4 Sect Post Liber 1, Page 438 Fd Co. Mon Cap Sp. Pine 6" N13" W 28 Lks 8" Red Pine N45" W 29.43" 10" Red Pine S40" W 49.10" 12" Ked Pine S40" E 26.98" 10" Red Pine N80" E 28.85" B. Description of comer evidence found and/or method applied in restoring or reestablishing corner. A4 Found 4" Conc Mon/Brass Cap in Place N77" E 28.87" 14" Red Pine S35" E 26.78" 15" Red Pine S49" W 49" Stump/Face Blaze C. Description of monument for corner and accessories established to perpetuate locating the position of the corner. A4 4" Conc Mon/Brass Cap S40" W 33.93" 14" Norway N34" W 61.78" 11" Norway N37" E 28.87" 14" Red Pine *Witness tags & nails used.	5. Private Claims	leu riat		A B C D E F G H I J K
Detailer E. Porter is a feed surveyor Nov. 10 1999 on berevy stals that under regularments of PA. A Melbrage PA. of 1970, he come points mentioned in lives 1 and 2 above were in conformance with regulations and niles therefore as required from the corner points mentioned in lives 1 and 2 above were in the conformance with regulations and niles therefore as required from the corner points mentioned in lines 3,4 and 5 above were in conformance with regulations of the Michigan Board of Land Surveyors or by a Bocrese of a Court of Law, established, re-established, monumented, necessed below. NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate. A decoration of original monument and accessories and/or subsequent restoration: A -4 GLO Notes - 1855				2 6 5 4 3 2
requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lies 1 and 2 above were in conformance with the claim regulations and rules therefore as required in the current mental of survey instructions of the United States Department of the Interformance of the United States Department of the Interformance of the United States Department of the Interformance of the Court of Law and for that the course proteins mentioned in lines 3.4 and 5 allows were in conformance with the clase of the Michigan recovered, found as expressed below. NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: A-4 GLO Notces — 1855 Set 1/4 Sect Post Liber 1, Page 438 Sp. Pine 6" N13" W 28 Lks 8" Red Pine N45" W 29, 43" 10" Red Pine S40" E 26, 98! 10" Red Pine S40" E 26, 98! 10" Red Pine S40" E 26, 98! 10" Red Pine S40" E 28, 85' B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: A-4 Found 4" Conc Mon/Brass Cap in Place N77" E 28.87" 14" Red Pine S35" E 26.78" 15" Red Pine S49" W 49" Stump/Face Blaze **Witness tags & nails used. *Witness tags & nails used. Date **Witness tags & nails used.	Delmer F Porter	cin a fold aunman Nozz 1	0.40.00	
United States Department of the literior, Sureau of Land Management or by a decree of a Court of Law and for that the corner protise mentioned in hies 3, 4 and 5 above were in conformance with the rules of the Michigan Bloard of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, receitablished, monumented, on this certificate. NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: A-4 CLO Notes - 1855 H. Fluharty #18223 Set 1/4 Sect Post Liber 1, Page 438 Sp. Pine 6" N13° W 28 Lks 8" Red Pine N45° W 29.43' 10" Red Pine N50° E 28.85' B. Description of comer evidence found and/or method applied in restoring or reestablishing corner: A-4 Found 4" Conc Mon/Brass Cap in Place N77° E 28.87' 14" Red Pine S35° E 26.78' 15" Red Pine S49° W 49' Stump/Face Blaze C. Description of monument for corner and accessories established to perpetuate locating the position of the corner. A-4 4" Conc Mon/Brass Cap Surveyor No. 15410 LAND SURVEYOR No. 15410 **Witness tags & nails used. Date **Witness tags & nails used.	requirements of P.A. 74, Michigan	P.A. of 1970, the corner points me	ntioned in lines 1 and 2 above wer	ra in
Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below. NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate. A Description of original monument and accessories and/or subsequent restoration: A-4 GLO Notes - 1855 Set 1/4 Sect Post Liber 1, Page 438 Sp. Pine 6" N13°W 28 Lks 8" Red Pine N45°W 29,43' 10" Red Pine N45°W 29,43' 10" Red Pine N80°E 28.85' B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: A-4 Found 4" Conc Mon/Brass Cap in Place N77°E 28.87' 14" Red Pine S49°W 49' Stump/Face Blaze C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: A-4 4" Conc Mon/Brass Cap S40°W 33.93' 14" Norway N34°W 61.78' 11" Norway N37°E 28.87' 14" Norway N37°E 28.87' 15" Red Pine Norway N37°E 28.87' 14" Norway N37°E 28.87' 15" Red Pine Norway N37°E 28.87' 14" Norway N37°E 28.87' 15" Red Pine Norway N38°E 26.78' 15" Red Pine Norway N39°E 26.78' 15" Red Pine N35°E 26.78' 15" Red Pine N35°E 26.78' 15" Red Pine N35°E 26.78' 15" Red Pine N36°E 26.78' 15" Red Pine N36°E 26.78' 15" Red Pine N37°E 28.87' 14" Norway N39°E 26.78' 15" Red Pine N39°E 26.78' 15" Red	United States Department of the In-	terior, Bureau of Land Management (of by a decree of a Court of Law are	tion of the land of the land
NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate. A Description of original monument and accessories and/or subsequent restoration: A-4 GLO Notes - 1855	Board of Land Surveyors or by a	a Decree of a Court of Law; estail	ormance with the rules of the Michi blished, re-established, monumen	ted, 7
A. Description of original monument and accessories and/or subsequent restoration: A-4 CLO Notes - 1855	• • • • • • • • • • • • • • • • • • • •			
A. Description of original monument and accessories and/or subsequent restoration: A-4 GLO Notes - 1855 Set 1/4 Sect Post Liber 1, Page 438 Sp. Pine 6" \$22° 26 Lks Fd Co. Mon Cap Sp. Pine 6" N13° W 28 Lks Red Pine N45° W 29.43' 10" Red Pine \$50° W 49.10' 12" Red Pine \$50° E 28.85' B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: A-4 Found 4" Conc Mon/Brass Cap in Place N77° E 28.87' 14" Red Pine S35° E 26.78' 15" Red Pine S49° W 49' Stump/Face Blaze C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: A-4 4" Conc Mon/Brass Cap S40° W 33.93' 14" Norway N34° W 61.78' 11" Norway N34° W 61.78' 11" Norway N34° W 61.78' 11" Norway N35° E 26.78' 15" Red Pine *Witness tags & nails used. Signed by Alamas Andrea *Witness tags & nails used.		irs, all in the same town and range	e, may be recorded	
A. Description of original monument and accessories and/or subsequent restoration: A-4 GLO Notes - 1855			•	
A Description of original monument and accessories and/or subsequent restoration: A-4 GLO Notes - 1855				12 31 32 33 34 35
Set 1/4 Sect Post Sp. Pine 6" S22°W 26 Lks Sp. Pine 6" S22°W 26 Lks Sp. Pine 6" N13°W 28 Lks Sp. Pine 6" N13°W 29.43' 10" Red Pine N50°W 29.43' 10" Red Pine S40°E 26.98' 10" Red Pine N80°E 28.85' B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: A-4 Found 4" Conc Mon/Brass Cap in Place N7°E 28.87' 14" Norway N7°E 28.87' 15" Red Pine *Witness tags & nails used.	A. Description of original mon	ument and accessories and/or s	ubsequent restoration:	131
A-4 Found 4" Conc Mon/Brass Cap in Place N77° E 28.87' 14" Red Pine S35° E 26.78' 15" Red Pine S49° W 49' Stump/Face Blaze C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: A-4 4" Conc Mon/Brass Cap S40° W 33.93' 14" Norway N34° W 61.78' 11" Norway N77° E 28.87' 14" Norway N77° E 28.87' 14" Norway S35° E 26.78' 15" Red Pine *Witness tags & nails used. *Witness tags & nails used.	Set 1/4 Sec Sp. Pine 6"	t Post S22°W 26 Lks	Liber 1, Page 4 Fd Co. Mon Cap 8" Red Pine N45 10" Red Pine S5 12" Red Pine S4	438 5°W 29.43' 50°W 49.10' 40°E 26.98'
A-4 Found 4" Conc Mon/Brass Cap in Place N77° E 28.87' 14" Red Pine S35° E 26.78' 15" Red Pine S49° W 49' Stump/Face Blaze C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: A-4 4" Conc Mon/Brass Cap S40° W 33.93' 14" Norway N34° W 61.78' 11" Norway N77° E 28.87' 14" Norway N77° E 28.87' 14" Norway S35° E 26.78' 15" Red Pine *Witness tags & nails used. *Witness tags & nails used.	B. Description of corner evide	ence found and/or method applic	ed in restoring or reestablishing	corner: OF MICHIGAN
A-4 4" Conc Mon/Brass Cap S40° W 33.93' 14" Norway N34° W 61.78' 11" Norway N77° E 28.87' 14" Norway S35° E 26.78' 15" Red Pine *Witness tags & nails used. Signed by Allmu E Anta Date 1-15-99	A-4 Found 4" Co N77° E 28.87 S35° E 26.78	nc Mon/Brass Cap : ' 14" Red Pine ' 15" Red Pine	_	DELMER E. PORTER LAND SURVEYOR No. 15410
A-4 4" Conc Mon/Brass Cap S40° W 33.93' 14" Norway N34° W 61.78' 11" Norway N77° E 28.87' 14" Norway S35° E 26.78' 15" Red Pine *Witness tags & nails used. Signed by Allmu E Anta Date 1-15-99	C. Description of monument fo	ர corner and accessories establi	shed to perpetuate locating the	e position of the corner:
N34° W 61.78' 11" Norway N77° E 28.87' 14" Norway S35° E 26.78' 15" Red Pine *Witness tags & nails used. Signed by Delance E Anta Date 11-15-99	A-4 4" Conc Mon	/Brass Cap	F	Ratified by Peer Group
N77° E 28.87' 14" Norway S35° E 26.78' 15" Red Pine *Witness tags & nails used. Signed by Delanu E Anta Date 11-15-99			i	n accordance with P.A. 345
*Witness tags & nails used. Signed by Delmu & Police 11-15-99	N77° E 28.87	' 14" Norway		Chairman Nomian Schaus
Signed by Delmu & Pote 11-15-99	535°E 26.78			
		*Witnes	ss tags & nails v	ised.
	Signed by A Do Dags 4.	15 Pota	D.J.	11-15-90
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	±15410	Date	11-12-14